

I hereby certify that this paper is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR § 1.10 on the date indicated below and is addressed to "Commissioner for Patents, Washington, DC 20231."

Atty No. YOR920000693US2  
R&A No. 5075-0029.20

"Express Mail" Mailing Label No.: EL 910 311 355 US

Date of Deposit: 02-19-02

SAM PEN

Printed Name of Person Mailing Paper or Fee

Sam Pen  
Signature of Person Mailing Paper or Fee

CONTINUATION-IN-PART PATENT APPLICATION

**SUBSTANTIALLY TRANSPARENT AQUEOUS BASE SOLUBLE POLYMER SYSTEM FOR  
USE IN 157 NM RESIST APPLICATIONS**

Inventor(s): Ratnam Sooriyakumaran  
Robert David Allen  
Debra Fenzel-Alexander

Prepared by J. Elin Hartrum  
Registration No. 43,663  
REED & ASSOCIATES  
800 Menlo Avenue, Suite 210  
Menlo Park, California 94025  
(650) 330-0900 Telephone  
(650) 330-0980 Facsimile

10079289-021902

SUBSTANTIALLY TRANSPARENT AQUEOUS BASE SOLUBLE POLYMER SYSTEM  
FOR USE IN 157 NM RESIST APPLICATIONS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This is a continuation-in-part of U.S. Patent Application Serial No. 09/748,071, filed December 21, 2000, the disclosure of which is incorporated by reference in its entirety.

TECHNICAL FIELD

[0002] This invention relates generally to the fields of polymer chemistry, lithography, and semiconductor fabrication. More particularly, the invention relates to the synthesis of a silicon-containing polymer system with a silsesquioxane (SSQ) backbone that is substantially transparent at 157 nm and is useful in lithographic photoresist compositions, particularly single and bilayer chemical amplification photoresist compositions including ultraviolet, electron-beam, and x-ray photoresists.

10079229-021902

### BACKGROUND

[0003] There is a desire in the industry for higher circuit density in microelectronic devices made using lithographic techniques. One method of increasing the number of components per chip is to decrease the minimum feature size on the chip, which requires higher lithographic resolution. It is known in the art that increasing the numerical aperture (NA) of the lens system of the lithographic imaging tool increases the resolution at a given wavelength. However, increasing the NA results in a decrease in the depth of focus (DOF) of the imaging radiation, thereby requiring a reduction in the thickness of the imaging resist film. A decrease in the resist film thickness can lead to problems in subsequent processing steps (e.g., ion implantation and etching).

[0004] In order to overcome these problems, bilayer resists have been developed. Such bilayer resists are generally comprised of a top thin film imaging layer coated on a thick organic underlayer and are patterned by i) imagewise exposure and development of the top layer, and then (ii) anisotropically transferring the developed pattern in the top layer to the thick underlayer and subsequently to the substrate. The top imaging layer contains a suitable refractory oxide precursor such as silicon, boron or germanium that enables the use of oxygen-reactive ion etching (RIE) in the image transfer step.

[0005] Additionally, over the past twenty years there has been an industry-wide shift to shorter wavelength exposure systems that also results in a decrease in the DOF. This has been accomplished by reducing the wavelength of the imaging radiation from the visible (436 nm) down through the ultraviolet (365 nm) to the deep ultraviolet (DUV) at 248 nm. Ultra-deep ultraviolet radiation, particularly 193 nm, is now known. See, for example, Allen et al. (1995), "Resolution and Etch Resistance of a Family of 193 nm Positive Resists," *J. Photopolym. Sci. and Tech.* 8(4):623-636, and Abe et al. (1995), "Study of ArF Resistant Material in Terms of Transparency and Dry Etch Resistance," *J. Photopolym. Sci. and Tech.* 8(4):637-642.

[0006] However, as the desired feature size decreases, the resolution capability of even these resists is not sufficient to yield sufficiently small features and the next generation of optical lithography tools under development will employ an F<sub>2</sub> 157 nm laser as the exposure source. Due to the very poor transparency of conventional resists at this wavelength, new polymer systems will have to be defined. The challenge in developing single and bilayer chemically amplified resists for 157 nm lithography is in achieving suitable transparency in polymers that have acid-labile functionalities or crosslinking groups and thereby convert to materials that are either soluble, when used as a positive resist, or insoluble when used as a negative resist, in industry standard developers.

[0007] Studies, such as Kunz et al (1999), *Proc. SPIE* 13:3678 and Crawford et al (2000), *Proc. SPIE* 357:3999 have identified two main classes of polymeric materials that are sufficiently transparent at 157 nm to be useful in single and bilayer resists; fluorocarbon polymers, and polysiloxanes (including polysilsesquioxanes). In the case of bilayer resists, siloxanes and silsesquioxanes are particularly advantageous because of their high silicon content. Specifically, polysilsesquioxanes will be ideal candidates for 157 nm bilayer resist development, as well as single layer resist development, because generally they have higher Tg than the polysiloxanes.

Sub 22 ✓  
[0008] Fluorocarbon polymers, such as polymers prepared from trifluoromethyl-substituted acrylates have been described previously. See, for example, Ito et al. (1981), "Methyl Alpha-Trifluoromethylacrylate, an E- Beam and UV Resist," *IBM Technical Disclosure Bulletin* 24(4):991, Ito et al. (1982) *Macromolecules* 15:915-920, which describes preparation of poly(methyl  $\alpha$ - trifluoromethylacrylate) and poly( $\alpha$ -trifluoromethylacrylonitrile) from their respective monomers, and Ito et al. (1987), "Anionic Polymerization of  $\alpha$ -(Trifluoromethyl)Acrylate," in *Recent Advances in Anionic Polymerization*, T. E. Hogen-Esch and J. Smid, Eds. (Elsevier Science Publishing Co., Inc.), which describes an anionic polymerization method for preparing polymers of trifluoromethylacrylate. Willson et al., *Polymer Engineering and Science* 23(18):1000-1003, also discuss poly(methyl  $\alpha$ -trifluoromethylacrylate) and the use thereof in a positive electron beam resist.

[0009] Photoresists comprised of silsesquioxane polymers have also been previously described. See, for example, U.S. Patent No. 6,087,064 to Lin et al., U.S. Patent No. 5,385,804 to Premalatha et al., U.S. Patent No. 5,338,818 to Brunsvold et al., and U.S. Patent No. 5,399,462 to Sachdev et al., which disclose the use of aryl or benzyl substituted polysilsesquioxanes in photo resists. However, none of these references disclose utility of fluorocarbonol and/or fluoroacid functionalized polysilsesquioxanes in 157 nm single and bilayer resist applications.

#### SUMMARY OF THE INVENTION

[0010] Accordingly, it is a primary object of the invention to address the above-described need in the art by providing novel fluorocarbonol- and/or fluoroacid-functionalized silsesquioxane polymers suitable for use in lithographic photoresist compositions.

[0011] It is another object of the invention to provide a lithographic photoresist composition containing fluorocarbonol- and/or fluoroacid-functionalized silsesquioxane polymers.

[0012] It is yet another object of the invention to provide such a composition wherein the fluorocarbonol- and/or fluoroacid-functionalized silsesquioxane polymer is a copolymer of a fluorocarbonol-functionalized silsesquioxane monomer and a silsesquioxane monomer substituted with an acid cleavable group.

[0013] It is yet another object of the invention to provide such a lithographic photoresist composition wherein the photoresist composition is a negative photoresist further comprising a crosslinking agent.

[0014] It is yet another object of the invention to provide such a lithographic photoresist composition wherein the photoresist composition is a single layer photoresist.

[0015] It is yet another object of the invention to provide such a lithographic photoresist composition wherein the photoresist composition is a bilayer photoresist.

[0016] It is still another object of the invention to provide a method for generating a resist image on a substrate using a photoresist composition as described herein.


[0017] It is a further object of the invention to provide a method for forming a patterned structure on a substrate by transferring the aforementioned resist image to the underlying substrate material, e.g., by etching.

[0018] Additional objects, advantages and novel features of the invention will be set forth in part in the description which follows, and in part will become apparent to those skilled in the art upon examination of the following, or may be learned by practice of the invention.

sub  
A3


[0019] In one aspect, then, the present invention relates to a fluorocarbonol and/or fluoroacid functionalized silsesquioxane polymer comprised of monomer units having structure (I)

(I)



Within structure (II), R<sup>1</sup>, R<sup>2</sup>, R<sup>3</sup> and R<sup>4</sup> are independently selected from the group consisting of substituents having structure (II)

(II)




wherein p is 0, 1, or 2, s is 0, 1, or 2, R<sup>7</sup> is hydrogen, alkyl or fluoroalkyl, R<sup>8</sup> is alkyl or fluoroalkyl, R<sup>9</sup> is OH, COOH or an acid-cleavable moiety, and Q is selected from the group consisting of substituted (e.g., fluorinated) and unsubstituted arylene, substituted (e.g.,



A3  
Cmt

fluorinated) and unsubstituted cycloalkylene, substituted and unsubstituted alkarylene, and moieties having the structure (III)

(III)




10079288-024920-0005120-00067007

wherein R<sup>5</sup> and R<sup>6</sup> are independently hydrogen, alkyl (e.g., linear, branched, or cycloalkyl) or fluoroalkyl and n is an integer from 1 to 4. The polymer may serve as either the base-soluble component of an unexposed resist in a negative resist or as an acid-labile material that releases acid following irradiation in a positive resist.

[0020] In another aspect of the invention, the present invention relates to a fluorocarbonol and/or fluoroacid functionalized silsesquioxane copolymer comprising monomer units having structure (I), as described above, and monomer units having structure (IV)

(IV)



Sub  
A  
CMT

wherein  $R^{10}$ ,  $R^{11}$ ,  $R^{12}$  and  $R^{13}$  are independently hydrogen, alkyl (e.g., linear, or branched, or cycloalkyl), fluoroalkyl, fluorocarbonol, fluoroacid or an acid-cleavable moiety, with the proviso that at least one of  $R^{10}$ ,  $R^{11}$ ,  $R^{12}$  and  $R^{13}$  is an acid-cleavable moiety. The copolymer may serve as an acid-labile material that releases acid following irradiation.

10079280-021802  
20061220-000000

[0021] In another aspect, the invention relates to a positive lithographic photoresist composition comprising a fluorocarbonol functionalized silsesquioxane polymer or copolymer as described above and a photosensitive acid generator (also referred to herein as a "photoacid generator," a "PAG," or a "radiation-sensitive acid generator").

[0022] In another aspect, the invention relates to a negative lithographic photoresist composition comprising a fluorocarbonol-functionalized silsesquioxane polymer as described above and a crosslinking agent.

Sub  
AS

[0023] The present invention also relates to the use of the resist composition in a lithography method. The process involves the steps of (a) optionally coating a substrate with an organic underlayer; (b) coating the organic underlayer with a top layer comprising: i) a radiation sensitive

Sub  
#5  
Cont

acid generator and ii) a fluorocarbonol functionalized silsesquioxane polymer containing polar groups and acid-labile groups; (b) exposing the top layer selectively to a predetermined pattern of radiation to form a latent image therein; (c) developing the image in the top layer using a suitable developer composition; and (e) transferring the image to the substrate. The resist composition may be used to form a single layer photoresist or a bilayer photoresist.

Sub  
#10079289-021002

[0024] The radiation may be ultraviolet, electron beam or x-ray. Ultraviolet radiation is preferred, particularly deep ultraviolet radiation having a wavelength of less than about 250 nm, e.g., 157 nm, 193 nm, or 248 nm. The pattern from the resist structure may then be transferred to the underlying substrate. Typically, the transfer is achieved by reactive ion etching or some other etching technique. Thus, the compositions of the invention and resulting resist structures can be used to create patterned material layer structures such as metal wiring lines, holes for contacts or vias, insulation sections (e.g., damascene trenches or shallow trench isolation), trenches for capacitor structures, etc., as might be used in the design of integrated circuit devices.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Sub  
#7

[0025] Fig. 1 presents a graph illustrating the optical density of a polymer of the invention at a range of UV wavelengths.

Sub  
#10

[0026] Fig. 2 presents copolymer of the inventions with acid-cleavable pendent groups.

## DETAILED DESCRIPTION OF THE INVENTION

### OVERVIEW AND DEFINITIONS:

[0027] Before describing the present invention in detail, it is to be understood that this invention is not limited to specific compositions, components or process steps, as such may vary. It is also to be understood that the terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting.

[0028] It must be noted that, as used in this specification and the appended claims, the singular forms "a," "an" and "the" include plural referents unless the context clearly dictates otherwise. Thus, for example, reference to "a monomer" includes a combination of two or more monomers that may or may not be the same, a "photoacid generator" includes a mixture of two or more photoacid generators, and the like.

[0029] In describing and claiming the present invention, the following terminology will be used in accordance with the definitions set out below.

[0030] "Optional" or "optionally" means that the subsequently described event or circumstance may or may not occur, and that the description includes instances where said event or circumstance occurs and instances where it does not. For example, the phrase "optionally

substituted lower alkyl" means that a lower alkyl moiety may or may not be substituted and that the description includes both unsubstituted lower alkyl and lower alkyl where there is substitution.

[0031] The term "alkyl" as used herein refers to a branched or unbranched saturated hydrocarbon group of 1 to 24 carbon atoms, such as methyl, ethyl, *n*-propyl, isopropyl, *n*-butyl, isobutyl, *t*-butyl, octyl, decyl, tetradecyl, hexadecyl, eicosyl, tetracosyl and the like, as well as cycloalkyl groups such as cyclopentyl, cyclohexyl and the like. The term "lower alkyl" intends an alkyl group of 1 to 6 carbon atoms, and the term "lower alkyl ester" refers to an ester functionality -C(O)O-R wherein R is lower alkyl.

[0032] The term "alkylene" as used herein refers to a difunctional branched or unbranched saturated hydrocarbon group of 1 to 24 carbon atoms, such as methylene, ethylene, *n*-propylene, *n*-butylene, *n*-hexylene, decylene, tetradecylene, hexadecylene, and the like. The term "lower alkylene" refers to an alkylene group of one to six carbon atoms.

Sub  
H9

[0033] The term "fluorinated" refers to replacement of a hydrogen atom in a molecule or molecular segment with a fluorine atom. The term "fluoroalkyl" refers to an alkyl group wherein at least one hydrogen atom has been replaced with a fluorine atom and includes, for example, trifluoromethyl, difluoromethyl, 2,2,2-trifluoroethyl, pentafluoromethyl, 3,3,3-trifluoromethyl, etc.

Sub  
A-9  
cont

Similarly, the term "fluorocarbon" refers to an alcohol moiety in which at least one of the hydrogens bonded to a carbon atom has been replaced with a fluorine atom and includes, for example,  $-\text{CF}_2\text{OH}$ ,  $-\text{CH}(\text{CF}_3)-\text{OH}$ ,  $-\text{C}(\text{CF}_3)_2-\text{OH}$ ,  $-\text{CH}_2\text{CF}_2\text{OH}$ , etc. The term "fluoroacid" refers to a carboxylic acid substituent in which at least one of the hydrogens bonded to a carbon atom has been replaced with a fluorine atom and includes, for example,  $-\text{CF}_2\text{COOH}$ ,  $-\text{CH}(\text{CF}_3)-\text{COOH}$ ,  $-\text{C}(\text{CF}_3)_2-\text{COOH}$ ,  $-\text{CH}_2\text{CF}_2\text{COOH}$ , etc. The term "perfluorinated" is also used in its conventional sense to refer to a molecule or molecular segment wherein all hydrogen atoms are replaced with fluorine atoms. Unless otherwise indicated, "fluorinated" substituents (such as fluoralkyl and the like) include perfluorinated substituents.

10072289-021902

[0034] The term "aryl" as used herein refers to an aromatic species containing 1 to 5 aromatic rings, either fused or linked, and either unsubstituted or substituted with 1 or more substituents typically selected from the group consisting of halogen, alkyl, alkenyl, alkynyl, alkoxy, alkenyloxy, alkynyloxy, alkylthio, aryl, aralkyl, and the like. Preferred aryl substituents contain 1 to 3 fused aromatic rings, and particularly preferred aryl substituents contain 1 aromatic ring or 2 fused aromatic rings.

Sub  
A-10

[0035] The terms "aralkyl" and "alkaryl" refer to moieties containing both alkyl and aryl species, typically containing less than about 24 carbon atoms, and more typically less than about 12 carbon atoms in the alkyl segment of the moiety, and typically containing 1 to 5 aromatic rings.

Sub  
#10  
cont

The rings may be either unsubstituted or substituted with 1 or more substituents typically selected from the group consisting of halogen, haloalky, alkyl, alkenyl, alkynyl, alkoxy, alkenyloxy, alkynyloxy, alkylthio, aryl, aralkyl, and the like. The term "aralkyl" refers to aryl-substituted alkyl groups, while the term "alkaryl" refers to alkyl-substituted aryl groups. The terms "aralkylene" and "alkarylene" are used in a similar manner to refer to aryl-substituted alkylene and alkyl-substituted arylene moieties.

10079289-021902

[0036] The term "arylene" refers to a difunctional aromatic moiety; "monocyclic arylene" refers to a cyclopentylene or phenylene group. These groups may be substituted with up to four ring substituents as outlined above.

[0037] The term "polymer" is used to refer to a chemical compound that comprises linked monomers, and that may be linear, branched, or crosslinked.

[0038] The terms "photogenerated acid" and "photoacid" are used interchangeably herein to refer to the acid that is created upon exposure of the present compositions to radiation, i.e., as a result of the radiation-sensitive acid generator in the compositions.

[0039] The term "substantially transparent" as used to describe a polymer that is "substantially transparent" to radiation of a particular wavelength refers to a polymer that has an absorbance of


less than about 4.0/micron, preferably less than about 3.0/micron, most preferably less than about 2.5/micron, at a selected wavelength.

[0040] For additional information concerning terms used in the field of lithography and lithographic compositions, reference may be had to *Introduction to Microlithography*, Eds. Thompson et al. (Washington, D.C.: American Chemical Society, 1994).

**THE FLUOROCARBINOL- AND/OR FLUOROACID-FUNCTIONALIZED SILSESQUIOXANE POLYMERS:**

[0041] The fluorocarinol- and/or fluoroacid-functionalized silsesquioxane polymer comprised of a monomer unit having structure (I)


(I)



Within structure (I), R<sup>1</sup>, R<sup>2</sup>, R<sup>3</sup> and R<sup>4</sup> are independently selected from the group consisting of substituents having structure (II)




(II)



wherein p is 0, 1, or 2, s is 0, 1, or 2, R<sup>7</sup> is hydrogen, linear or branched alkyl, or fluoroalkyl, R<sup>8</sup> is alkyl or fluoroalkyl, R<sup>9</sup> is OH, COOH or an acid-cleavable moiety, and Q is selected from the group consisting of substituted and unsubstituted arylene, substituted and unsubstituted cycloalkylene, substituted and unsubstituted alkarylene, and moieties having the structure (III)

(III)



wherein R<sup>5</sup> and R<sup>6</sup> are independently hydrogen, alkyl (e.g., linear, branched, or cycloalkyl) or fluoroalkyl and n is an integer from 1 to 4.

[0042] Preferred R<sup>5</sup> and R<sup>6</sup> substituents are hydrogen, C<sub>1</sub>-C<sub>6</sub> alkyl and C<sub>1</sub>-C<sub>6</sub> fluoroalkyl. Most preferred R<sup>5</sup> and R<sup>6</sup> substituents are hydrogen, methyl, ethyl and trifluoromethyl-substituted C<sub>1</sub>-C<sub>6</sub> alkyl, such as trifluoromethyl, 2,2,2-trifluoroethyl, and 3,3,3-trifluoromethyl.

Sub  
A13

[0043] Preferred R<sup>7</sup> substituents are hydrogen, C<sub>1</sub>-C<sub>6</sub> alkyl and C<sub>1</sub>-C<sub>6</sub> fluoroalkyl. Most preferred R<sup>7</sup> substituents are hydrogen, methyl, ethyl and trifluoromethyl- substituted C<sub>1</sub>-C<sub>6</sub> alkyl, such as trifluoromethyl, 2,2,2-trifluoroethyl, and 3,3,3-trifluoromethyl.

Sub  
A14

[0044] Preferred R<sup>8</sup> substituents are C<sub>1</sub>-C<sub>6</sub> alkyl and C<sub>1</sub>-C<sub>6</sub> fluoroalkyl. Most preferred R<sup>8</sup> substituents are methyl, ethyl and trifluoromethyl- substituted C<sub>1</sub>-C<sub>6</sub> alkyl, such as trifluoromethyl, 2,2,2-trifluoroethyl, and 3,3,3-trifluoromethyl.

Sub  
A15

[0045] In structure (II) substituent, the R<sup>9</sup> moiety is -OH, -COOH, or an acid-cleavable moiety, i.e., a molecular moiety that is cleavable with acid, particularly photogenerated acid. Suitable acid-cleavable functionalities include, but are not limited to, esters of the formula -(L)<sub>v</sub>-(CO)-OR<sup>14</sup>, carbonates of the formula -(L)<sub>v</sub>-O-(CO)-O-R<sup>15</sup>, and ethers of the formula -OR<sup>16</sup>, wherein R<sup>14</sup>, R<sup>15</sup> and R<sup>16</sup> are selected so as to render the functionality acid-cleavable, v is zero or 1, and L is a linking group such as an alkylene group (e.g., linear, branched or cycloalkylene group such as norbornyl or cyclohexylene) a fluoroalkylene group, or an aryl group. In acid-cleavable ester groups, i.e., substituents having the formula -(L)<sub>v</sub>-(CO)-OR<sup>14</sup>, R<sup>14</sup> is preferably either a tertiary alkyl, e.g., *t*-butyl, a cyclic or alicyclic substituent (generally C<sub>7</sub>-C<sub>12</sub>) with a tertiary attachment point such as adamantyl, norbornyl, isobornyl, 2-methyl-2-adamantyl, 2-methyl-2-isobornyl, 2-butyl-2-adamantyl, 2-propyl-2-isobornyl, 2-methyl-2-tetracyclododecenyl, 2-methyl-2-dihydrodicyclopentadienyl-cyclohexyl,


Sub  
H15  
cont  
1-methylcyclopentyl or 1-methylcyclohexyl, or a 2-trialkylsilylethyl group, such as 2  
-trimethylsilyethyl, or 2-triethylsilylethyl.

---


[0046] Other examples of such acid-cleavable ester groups are set forth in U.S. Patent No. 4,491,628 to Ito et al., entitled "Positive- and Negative-Working Resist Compositions with Acid-Generating Photoinitiator and Polymer with Acid Labile Groups Pendant from Polymer Backbone," and in the *Handbook of Microlithography, Micromachining, and Microfabrication, Vol. 1: Microlithography*, Ed. P. Raj-Coudhury, p. 321 (1997). An exemplary acid-cleavable carbonate, i.e., a substituent having the formula  $-O-(CO)-O-R^{15}$ , is  $-O-t$ -butyloxycarbonyl ( $t$ -BOC) (in which case  $R^{15}$  is  $t$ -butyl), and exemplary ethers, i.e.,  $-OR^{16}$  moieties, are tetrahydropyranyl ether (in which case  $R^{16}$  is tetrahydropyranyl) and trialkylsilyl ethers (in which case  $R^{16}$  is a trialkylsilyl such as trimethylsilyl). Other suitable acid-labile protecting groups may be found in U.S. Patent No. 5,679,495 to Yamachika et al. or in the pertinent literature and texts, e.g., Greene et al., *Protective Groups in Organic Synthesis*, 2<sup>nd</sup> Ed. (New York: John Wiley & Sons, 1991).

[0047] Preferred acid-cleavable pendant groups are organic ester groups that undergo a cleavage reaction in the presence of photogenerated acid to generate a carboxylic acid group. Thus, in a preferred embodiment,  $R^9$  is  $-(L)_n-(CO)-OR^{14}$  wherein  $L$ ,  $n$  and  $R^{14}$  are as defined above.

[0048] Example substituents having structure (II) include, but are not limited to,




Sub  
A 16  
cont



[0049] Additionally, the structure (I) monomer units may be used to form a fluorocarinol-functionalized copolymer comprised of structure (I) monomer units and monomer units having structure (IV)

(IV)



in which  $R^{10}$ ,  $R^{11}$ ,  $R^{12}$  and  $R^{13}$  are independently hydrogen, alkyl (e.g., linear, branched, or cycloalkyl), fluoroalkyl, fluorocarinol, fluoroacid, or an acid-cleavable moiety, with the proviso that at least one of  $R^{10}$ ,  $R^{11}$ ,  $R^{12}$  and  $R^{13}$  is an acid-cleavable moiety. It will be apparent from the structures and aforementioned definitions that these monomer units may or may not be fluorinated. The silsesquioxane polymers and copolymers represented by structures (I) and (IV)

are not limited to any particular architecture or structure. It is intended to include all possible architectures and structures of the polymer including random copolymers, block copolymers, ladder structures, cage structures, partial cage structures, and random SSQ structures.

Sub  
#17  
10079229-021902

[0050] The polymer and copolymer may comprise different monomer units each having structure (I), and, in the case of the copolymer, different monomer units each having structure (IV). The polymer and copolymer may also comprise one or more other monomer units, typically formed from addition polymerizable monomers, preferably vinyl monomers, for example, to enhance the performance of the photoresist. Thus, the polymer and copolymer may comprise minor amounts of acrylic acid or methacrylic acid monomer (e.g., 5-30%) to enhance development.

[0051] The polymer and copolymer may also comprise other suitable monomer units such as hydroxystyrene to enhance development and etch resistance or a silicon-containing monomer unit (e.g., a silicon-containing acrylate, methacrylate, or styrene) to enhance oxygen plasma etch resistance for bilayer applications. In general, suitable comonomers include, but are not limited to, the following ethylenically unsaturated polymerizable monomers: acrylic and methacrylic acid esters and amides, including alkyl acrylates, aryl acrylates, alkyl methacrylates and aryl methacrylates (for example, methyl acrylate, methyl methacrylate, *n*-butyl acrylate, *n*-butyl methacrylate, *t*-butyl acrylate, *t*-butyl methacrylate, 2-ethylhexyl methacrylate, benzyl acrylate and *N*-phenylacrylamide); vinyl aromatics, including unsubstituted styrene and styrene

substituted with one or two lower alkyl, halogen or hydroxyl groups (for example, styrene derivatives such as 4-vinyltoluene, 4-vinylphenol,  $\alpha$ -methylstyrene, 2,5-dimethylstyrene, 4-*t*-butylstyrene and 2-chlorostyrene); butadiene; vinyl acetate; vinyl bromide; vinylidene chloride; and C<sub>5</sub>-C<sub>20</sub>, generally C<sub>7</sub>-C<sub>15</sub>, cyclic olefin monomers such as norbornene and tetracyclododecane; fluorinated analogs of any of the foregoing, e.g., fluorinated acrylic and methacrylic acid esters; and others readily apparent to one skilled in the art. For use in 157 nm lithography, fluorinated comonomers are preferred.

#### MONOMER SYNTHESIS AND POLYMERIZATION:

[0052] The present polymers and copolymers may be readily synthesized using methods described in the pertinent texts and literature, or as known to those of ordinary skill in the art. Methods for synthesizing representative monomers are described in the examples, as are methods for preparing the fluorocarbonol-functionalized silsesquioxane polymers and copolymers. As illustrated in the Examples, the polymers are generally formed in a multi-step process. First, a protected version of a desired structure (II) substituent (e.g., wherein an OH or COOH is esterified) is reacted with a trihalosilane to form a protected structure (II)-substituted trihalosilane. Next, the substituted trihalosilane is hydrolyzed and the resulting compound polymerized via condensation polymerization to form a protected version of the polymer or copolymer. Finally, the protecting group is removed thus resulting in the final polymer or copolymer. The resulting polymer or copolymer typically has an average molecular weight in the

range of approximately 500 to 25,000, and generally in the range of approximately 1,000 to 5,000.

**THE PHOTOACID GENERATOR:**

[0053] The second component of the resist composition is a photoacid generator. Upon exposure to radiation, the photoacid generator generates a strong acid. A variety of photoacid generators can be used in the composition of the present invention. Generally, suitable acid generators have a high thermal stability (preferably to temperatures greater than 140 °C) so they are not degraded during pre-exposure processing. Generally, sulfonate compounds are preferred PAGs, particularly sulfonate salts, but other suitable sulfonate PAGs include sulfonated esters and sulfonyloxy ketones. See U.S. Patent No. 5,344,742 to Sinta et al., and *J. Photopolymer Science and Technology*, 4:337-340 (1991), for disclosure of suitable sulfonate PAGs, including benzoin tosylate, t-butylphenyl  $\alpha$ -(p-toluenesulfonyloxy)-acetate and t-butyl  $\alpha$ -(p-toluenesulfonyloxy)-acetate.

[0054] Onium salts are also generally preferred acid generators of compositions of the invention. Onium salts that are weakly nucleophilic anions have been found to be particularly suitable. Examples of such anions are the halogen complex anions of divalent to heptavalent metals or non-metals, for example, Sb, B, P, and As. Examples of suitable onium salts are aryl-diazonium salts, halonium salts, aromatic sulfonium salts, aromatic sulfoxonium salts, and selenium salts



(e.g., triarylsulfonium and diaryliodonium hexafluoroantimonates, hexafluoroarsenates, trifluoromethanesulfonates and others). Examples of suitable preferred onium salts can be found in U.S. Patent Nos. 4,442,197, 4,603,101, and 4,624,912.

Sub  
A10  
[0055] Other useful acid generators include the family of nitrobenzyl esters and the s-triazine derivatives. Suitable s-triazine acid generators are disclosed, for example, in U.S. Patent No. 4,189,323.

10079289-021002  
Still other suitable acid generators include N-camphorsulfonyloxynaphthalimide, N-pentafluorophenylsulfonyloxynaphthalimide, ionic iodonium sulfonates, e.g., diaryl iodonium (alkyl or aryl) sulfonate and bis-(di-*t*-butylphenyl)iodonium camphanylsulfonate, perfluoroalkanesulfonates, such as perfluoropentanesulfonate, perfluorooctanesulfonate, perfluoromethanesulfonate; aryl (e.g., phenyl or benzyl) triflates and derivatives and analogs thereof, e.g., triphenylsulfonium triflate or bis-(*t*-butylphenyl)iodonium triflate; pyrogallol derivatives (e.g., trimesylate of pyrogallol); trifluoromethanesulfonate esters of hydroxyimides,  $\alpha,\alpha'$ -bis-sulfonyl-diazomethanes; sulfonate esters of nitro-substituted benzyl alcohols; naphthoquinone-4-diazides; and alkyl disulfones. Other suitable photoacid generators are disclosed in Reichmanis et al. (1991), *Chemistry of Materials* 3:395, and in U.S. Patent No. 5,679,495 to Yamachika et al. Additional suitable acid generators useful in conjunction with the

Sub  
A13  
cont  
compositions and methods of the invention will be known to those skilled in the art and/or are described in the pertinent literature.

**THE PHOTORESIST COMPOSITION:**

Sub  
A19  
10075223  
00000000  
[0056] The photoresist composition herein comprises both a fluorocarbonol- and/or fluoroacid-functionalized silsesquioxane polymer or copolymer as described in detail above, and an acid generator, with the polymer or copolymer representing up to about 99.5 wt.% of the solids included in the composition, and the photoacid generator representing approximately 0.5-10 wt.% of the solids contained in the composition. The photoresist may take the form a negative or a positive photoresist and other components and additives may also be present.

Sub  
A20  
10075223  
00000000  
[0057] If the photoresist is a positive photoresist, the composition may include a monomeric or polymeric acid-cleavable dissolution inhibitor. When the resist-coated substrate is patternwise exposed to a radiation source, the acid generated by the radiation-sensitive acid generator will cleave the acid-cleavable moieties in the polymer or copolymer and/or in the dissolution inhibitor, thus making the exposed areas of the photoresist composition soluble in conventional developer solutions. If included, the dissolution inhibitor, may be present either as pendent moiety on the polymer or copolymer chain, as an additional element in the photoresist composition, or as a combination of the two. If a dissolution inhibitor is present, it will typically represent in the range of about 1 wt.% to 40 wt.%, preferably about 5 wt.% to 30 wt.%, of the

Sub  
Area  
cont

total solids. Positive photoresist compositions that comprise a dissolution inhibitor need not have acid-cleavable moieties on the silsesquioxane polymer, i.e. R<sup>9</sup> need not be an acid-labile group, as the dissolution inhibitor will independently be sufficient to result in the dissolution of the exposed areas of resist.

[0058] Suitable dissolution inhibitors are known to those skilled in the art and/or described in the pertinent literature. Preferred dissolution inhibitors have high solubility in the resist composition and the solvent used to prepare solutions of the resist composition (e.g., propylene glycol methyl ether acetate, or "PGMEA"), exhibit strong dissolution inhibition, have a high exposed dissolution rate, are transparent at the wavelength of interest, exhibit a moderating influence on T<sub>g</sub>, strong etch resistance, and display good thermal stability (i.e., stability at temperatures of about 140°C or greater). Both polymeric and monomeric dissolution inhibitors may be used in the photoresist composition of the invention.



[0059] Suitable dissolution inhibitors include, but are not limited to, bisphenol A derivatives and carbonate derivatives wherein the hydroxyl group of bisphenol A (Bis-A) is replaced by tert-butyl derivative substituents such as tert-butyloxy, tert-butyloxycarbonyl, and tert-butyloxycarbonyl-methyl groups; fluorinated bisphenol A derivatives such as CF<sub>3</sub>-Bis-A/tBuOCOCH<sub>3</sub> (6F-Bisphenol A protected with a *t*-butoxycarbonylmethyl group); linear or branched chain acetal groups such as 1-ethoxyethyl, 1-propoxyethyl, 1-n-butoxyethyl,

1-isobutoxy-ethyl, 1-tert-butyloxyethyl, and 1-tert-amxyloxyethyl groups; and cyclic acetal groups such as tetrahydrofuranyl, tetrahydropyranyl, and 2-methoxytetrahydropyranyl groups; and androstane-17-alkylcarboxylates and analogs thereof, wherein the 17-alkylcarboxylate at the 17-position is typically lower alkyl. Examples of such compounds include lower alkyl esters of cholic, ursocholic and lithocholic acid, including methyl cholate, methyl lithocholate, methyl ursocholate, *t*-butyl cholate, *t*-butyl lithocholate, *t*-butyl ursocholate, and the like (*see, e.g.*, Allen et al. (1995) *J. Photopolym. Sci. Technol.*, cited *supra*); hydroxyl-substituted analogs of such compounds (*ibid.*); and androstane-17-alkylcarboxylates substituted with 1 to 3 C<sub>1</sub>-C<sub>4</sub> fluoroalkyl carbonyloxy substituents, such as *t*-butyl trifluoroacetylithocholate (*see, e.g.*, U.S. Patent No. 5,580,694 to Allen et al.).





[0060] In the event the composition is to be used as a negative photoresist, the composition will include a crosslinking agent. When the resist-coated substrate is exposed to radiation, the acid produced by the radiation-sensitive acid generator in the exposed areas will cause the crosslinking agent to react with the polymers of the invention, thus making the exposed regions insoluble in developer solution. As with dissolution inhibitors the crosslinking agent, when present, will typically represent in the range of about 1 wt.% to 40 wt.%, preferably about 5 wt.% to 30 wt.%, of the total solids. Dissolution inhibitors are not included in negative photoresists nor are crosslinking agents included in positive photoresists.

Sub  
A21

[0061] The crosslinking agent may be any suitable crosslinking agent known in the negative photoresist art that is otherwise compatible with the other components of the photoresist composition. The crosslinking agent preferably acts to crosslink the polymer component in the presence of a generated acid. Preferred crosslinking agents are glycoluril compounds such as tetramethoxymethyl glycoluril, methylpropyltetramethoxymethyl glycoluril, and methylphenyltetramethoxymethyl glycoluril, available under the POWDERLINK<sup>(R)</sup> trademark from American Cyanamid Company. Other possible crosslinking agents include, but are not limited to: 2,6-bis(hydroxymethyl)-p-cresol and compounds having the following structures:



Sub  
A21  
cont



including their analogs and derivatives, such as those found in Japanese Laid-Open Patent Application (Kokai) No. 1-293339, as well as etherified amino resins, for example, methylated or butylated melamine resins (N-methoxymethyl- or N-butoxymethyl-melamine respectively) or methylated/butylated glycolurils, for example as can be found in Canadian Patent No. 1 204 547. Combinations of crosslinking agents may be used.

[0061] The remainder of the composition is composed of a solvent and may additionally, if necessary or desirable, include customary additives such as dyes, sensitizers, additives used as

stabilizers and acid-diffusion controlling agents, coating aids such as surfactants or anti-foaming agents, adhesion promoters and plasticizers.

[0062] The choice of solvent is governed by many factors not limited to the solubility and miscibility of resist components, the coating process, and safety and environmental regulations. Additionally, inertness to other resist components is desirable. It is also desirable that the solvent possess the appropriate volatility to allow uniform coating of films yet also allow significant reduction or complete removal of residual solvent during the post-application bake process. See, *e.g.*, *Introduction to Microlithography*, Eds. Thompson et al., cited previously. Solvents may generally be chosen from ether-, ester-, hydroxyl-, and ketone-containing compounds, or mixtures of these compounds. Examples of appropriate solvents include cyclopentanone, cyclohexanone, lactate esters such as ethyl lactate, alkylene glycol alkyl ether esters such as propylene glycol methyl ether acetate, alkylene glycol monoalkyl esters such as methyl cellosolve, butyl acetate, 2-ethoxyethanol, and ethyl 3-ethoxypropionate. Preferred solvents include ethyl lactate, propylene glycol methyl ether acetate, ethyl 3-ethoxypropionate and their mixtures.

[0063] The above list of solvents is for illustrative purposes only and should not be viewed as being comprehensive nor should the choice of solvent be viewed as limiting the invention in any way. Those skilled in the art will recognize that any number of solvents or solvent mixtures may

10079289-021902

be used. Greater than 50 percent of the total mass of the resist formulation is typically composed of the solvent, preferably greater than 80 percent.

[0064] Other customary additives include dyes that may be used to adjust the optical density of the formulated resist and sensitizers which enhance the activity of photoacid generators by absorbing radiation and transferring it to the photoacid generator. Examples include aromatics such as functionalized benzenes, pyridines, pyrimidines, biphenylenes, indenenes, naphthalenes, anthracenes, coumarins, anthraquinones, other aromatic ketones, and derivatives and analogs of any of the foregoing.

[0065] A wide variety of compounds with varying basicity may be used as stabilizers and acid-diffusion controlling additives. They may include nitrogenous compounds such as aliphatic primary, secondary, and tertiary amines, cyclic amines such as piperidines, pyrimidines, morpholines, aromatic heterocycles such as pyridines, pyrimidines, purines, imines such as diazabicycloundecene, guanidines, imides, amides, and others. Ammonium salts may also be used, including ammonium, primary, secondary, tertiary, and quaternary alkyl- and arylammonium salts of alkoxides including hydroxide, phenolates, carboxylates, aryl and alkyl sulfonates, sulfonamides, and others. Other cationic nitrogenous compounds including pyridinium salts and salts of other heterocyclic nitrogenous compounds with anions such as



alkoxides including hydroxide, phenolates, carboxylates, aryl and alkyl sulfonates, sulfonamides, and the like may also be employed.

Sub  
H22  
10079289-021002

[0066] Surfactants may be used to improve coating uniformity, and include a wide variety of ionic and non-ionic, monomeric, oligomeric, and polymeric species. Likewise, a wide variety of anti-foaming agents may be employed to suppress coating defects. Adhesion promoters may be used as well; again, a wide variety of compounds may be employed to serve this function. A wide variety of monomeric, oligomeric, and polymeric plasticizers such as oligo- and polyethyleneglycol ethers, cycloaliphatic esters, and non-acid reactive steroidally-derived materials may be used as plasticizers, if desired.

[0067] However, neither the classes of compounds nor the specific compounds mentioned above are intended to be comprehensive and/or limiting. One versed in the art will recognize the wide spectrum of commercially available products that may be used to carry out the types of functions that these customary additives perform.

[0068] Typically, the sum of all customary additives (not including the PAG) will comprise less than 20 percent of the solids included in the resist formulation, and preferably less than 5 percent.

USE IN GENERATION OF RESIST IMAGES ON A SUBSTRATE:

Sub  
#23

[0069] The present invention also relates to a process for generating a resist image on a substrate comprising the steps of: (a) coating a substrate with a film comprising the resist composition of the present invention; (b) imagewise exposing the film to radiation; and (c) developing the image. The first step involves coating the substrate with a film comprising the resist composition dissolved in a suitable solvent. Suitable substrates are ceramic, metallic or semiconductive, and preferred substrates are silicon-containing, including, for example, silicon dioxide, silicon nitride, and silicon oxynitride. The substrate may or may not be coated with an organic anti-reflective layer prior to deposition of the resist composition. Alternatively, a bilayer substrate may be employed wherein a resist composition of the invention forms an upper resist layer (i.e., the imaging layer) on top of a bilayer substrate comprised of a base layer and underlayer that lies between the upper resist layer and the base layer. The base layer of the bilayer substrate is comprised of a suitable substrate material, and the underlayer of the bilayer substrate is comprised of a material that is highly absorbing at the imaging wavelength and compatible with the imaging layer. Conventional underlayers include cross-linked poly(hydroxystyrene), polyesters, polyacrylates, fluorinated polymers, cyclic-olefin polymers and the like including diazonaphthoquinone (DNQ)/novolak resist material.

[0070] Preferably, the surface of the coated or uncoated, single or bilayer substrate is cleaned by standard procedures before the film is deposited thereon. Suitable solvents for the composition

are as described in the preceding section, and include, for example, cyclohexanone, ethyl lactate, and propylene glycol methyl ether acetate. The film can be coated on the substrate using art-known techniques known in the art, such as spin or spray coating, or doctor blading. Preferably, before the film has been exposed to radiation, the film is heated to an elevated temperature of about 90-160°C for a short period of time, typically on the order of about 1 minute. The dried film has a thickness of about 0.01 to about 5.0 microns, preferably about 0.02 to about 2.5 microns, more preferably about 0.05 to about 1.0 microns, and most preferably about 0.10 to about 0.20 microns.

[0071] In the second step of the process, the film is imagewise exposed to radiation, i.e., UV, X-ray, e-beam, EUV, or the like. Preferably, ultraviolet radiation having a wavelength of about 157 nm to about 365 nm is used and most preferably ultraviolet radiation having a wavelength of about 157 nm or about 193 nm is used. Suitable radiation sources include mercury, mercury/xenon, and xenon lamps. The preferred radiation source is a KrF excimer laser or a F<sub>2</sub> excimer laser. If longer wavelength radiation is used, e.g., 365 nm, a sensitizer may be added to the photoresist composition to enhance absorption of the radiation. Conveniently, due to the enhanced radiation sensitivity of the photoresist composition, full exposure of the photoresist composition is achieved with less than about 100 mJ/cm<sup>2</sup> of radiation, more preferably with less than about 50 mJ/cm<sup>2</sup> of radiation.

[0072] The radiation is absorbed by the radiation-sensitive acid generator to generate free acid. In positive photoresists, with heating, the free acid causes cleavage of the acid-cleavable pendant groups that are present as either the R<sup>9</sup> moiety in the structure (II) substituent and/or as R<sup>10</sup>, R<sup>11</sup>, R<sup>12</sup> or R<sup>13</sup> in the structure (IV) monomer, resulting in the formation of the corresponding carboxylic acid. In negative photoresists, the free acid causes the crosslinking agents to react with the polymer, thereby forming insoluble areas of exposed photoresist. Preferably, after the photoresist composition has been exposed to radiation, the photoresist composition is again heated to an elevated temperature of about 90-150°C for a short period of time, on the order of about 1 minute.

5410  
5411  
5412  
5413  
5414  
5415  
5416  
5417  
5418  
5419  
5420  
5421  
5422  
5423  
5424  
5425  
5426  
5427  
5428  
5429  
5430  
5431  
5432  
5433  
5434  
5435  
5436  
5437  
5438  
5439  
5440  
5441  
5442  
5443  
5444  
5445  
5446  
5447  
5448  
5449  
5450  
5451  
5452  
5453  
5454  
5455  
5456  
5457  
5458  
5459  
5460  
5461  
5462  
5463  
5464  
5465  
5466  
5467  
5468  
5469  
5470  
5471  
5472  
5473  
5474  
5475  
5476  
5477  
5478  
5479  
5480  
5481  
5482  
5483  
5484  
5485  
5486  
5487  
5488  
5489  
5490  
5491  
5492  
5493  
5494  
5495  
5496  
5497  
5498  
5499  
5500  
5501  
5502  
5503  
5504  
5505  
5506  
5507  
5508  
5509  
5510  
5511  
5512  
5513  
5514  
5515  
5516  
5517  
5518  
5519  
5520  
5521  
5522  
5523  
5524  
5525  
5526  
5527  
5528  
5529  
5530  
5531  
5532  
5533  
5534  
5535  
5536  
5537  
5538  
5539  
5540  
5541  
5542  
5543  
5544  
5545  
5546  
5547  
5548  
5549  
5550  
5551  
5552  
5553  
5554  
5555  
5556  
5557  
5558  
5559  
5560  
5561  
5562  
5563  
5564  
5565  
5566  
5567  
5568  
5569  
5570  
5571  
5572  
5573  
5574  
5575  
5576  
5577  
5578  
5579  
5580  
5581  
5582  
5583  
5584  
5585  
5586  
5587  
5588  
5589  
5590  
5591  
5592  
5593  
5594  
5595  
5596  
5597  
5598  
5599  
5600  
5601  
5602  
5603  
5604  
5605  
5606  
5607  
5608  
5609  
5610  
5611  
5612  
5613  
5614  
5615  
5616  
5617  
5618  
5619  
5620  
5621  
5622  
5623  
5624  
5625  
5626  
5627  
5628  
5629  
5630  
5631  
5632  
5633  
5634  
5635  
5636  
5637  
5638  
5639  
5640  
5641  
5642  
5643  
5644  
5645  
5646  
5647  
5648  
5649  
5650  
5651  
5652  
5653  
5654  
5655  
5656  
5657  
5658  
5659  
5660  
5661  
5662  
5663  
5664  
5665  
5666  
5667  
5668  
5669  
5670  
5671  
5672  
5673  
5674  
5675  
5676  
5677  
5678  
5679  
5680  
5681  
5682  
5683  
5684  
5685  
5686  
5687  
5688  
5689  
5690  
5691  
5692  
5693  
5694  
5695  
5696  
5697  
5698  
5699  
5700  
5701  
5702  
5703  
5704  
5705  
5706  
5707  
5708  
5709  
5710  
5711  
5712  
5713  
5714  
5715  
5716  
5717  
5718  
5719  
5720  
5721  
5722  
5723  
5724  
5725  
5726  
5727  
5728  
5729  
5730  
5731  
5732  
5733  
5734  
5735  
5736  
5737  
5738  
5739  
5740  
5741  
5742  
5743  
5744  
5745  
5746  
5747  
5748  
5749  
5750  
5751  
5752  
5753  
5754  
5755  
5756  
5757  
5758  
5759  
5760  
5761  
5762  
5763  
5764  
5765  
5766  
5767  
5768  
5769  
5770  
5771  
5772  
5773  
5774  
5775  
5776  
5777  
5778  
5779  
5780  
5781  
5782  
5783  
5784  
5785  
5786  
5787  
5788  
5789  
5790  
5791  
5792  
5793  
5794  
5795  
5796  
5797  
5798  
5799  
5800  
5801  
5802  
5803  
5804  
5805  
5806  
5807  
5808  
5809  
5810  
5811  
5812  
5813  
5814  
5815  
5816  
5817  
5818  
5819  
5820  
5821  
5822  
5823  
5824  
5825  
5826  
5827  
5828  
5829  
5830  
5831  
5832  
5833  
5834  
5835  
5836  
5837  
5838  
5839  
5840  
5841  
5842  
5843  
5844  
5845  
5846  
5847  
5848  
5849  
5850  
5851  
5852  
5853  
5854  
5855  
5856  
5857  
5858  
5859  
5860  
5861  
5862  
5863  
5864  
5865  
5866  
5867  
5868  
5869  
5870  
5871  
5872  
5873  
5874  
5875  
5876  
5877  
5878  
5879  
5880  
5881  
5882  
5883  
5884  
5885  
5886  
5887  
5888  
5889  
5890  
5891  
5892  
5893  
5894  
5895  
5896  
5897  
5898  
5899  
5900  
5901  
5902  
5903  
5904  
5905  
5906  
5907  
5908  
5909  
5910  
5911  
5912  
5913  
5914  
5915  
5916  
5917  
5918  
5919  
5920  
5921  
5922  
5923  
5924  
5925  
5926  
5927  
5928  
5929  
5930  
5931  
5932  
5933  
5934  
5935  
5936  
5937  
5938  
5939  
5940  
5941  
5942  
5943  
5944  
5945  
5946  
5947  
5948  
5949  
5950  
5951  
5952  
5953  
5954  
5955  
5956  
5957  
5958  
5959  
5960  
5961  
5962  
5963  
5964  
5965  
5966  
5967  
5968  
5969  
5970  
5971  
5972  
5973  
5974  
5975  
5976  
5977  
5978  
5979  
5980  
5981  
5982  
5983  
5984  
5985  
5986  
5987  
5988  
5989  
5990  
5991  
5992  
5993  
5994  
5995  
5996  
5997  
5998  
5999  
6000  
6001  
6002  
6003  
6004  
6005  
6006  
6007  
6008  
6009  
6010  
6011  
6012  
6013  
6014  
6015  
6016  
6017  
6018  
6019  
6020  
6021  
6022  
6023  
6024  
6025  
6026  
6027  
6028  
6029  
6030  
6031  
6032  
6033  
6034  
6035  
6036  
6037  
6038  
6039  
6040  
6041  
6042  
6043  
6044  
6045  
6046  
6047  
6048  
6049  
6050  
6051  
6052  
6053  
6054  
6055  
6056  
6057  
6058  
6059  
6060  
6061  
6062  
6063  
6064  
6065  
6066  
6067  
6068  
6069  
6070  
6071  
6072  
6073  
6074  
6075  
6076  
6077  
6078  
6079  
6080  
6081  
6082  
6083  
6084  
6085  
6086  
6087  
6088  
6089  
6090  
6091  
6092  
6093  
6094  
6095  
6096  
6097  
6098  
6099  
6100  
6101  
6102  
6103  
6104  
6105  
6106  
6107  
6108  
6109  
6110  
6111  
6112  
6113  
6114  
6115  
6116  
6117  
6118  
6119  
6120  
6121  
6122  
6123  
6124  
6125  
6126  
6127  
6128  
6129  
6130  
6131  
6132  
6133  
6134  
6135  
6136  
6137  
6138  
6139  
6140  
6141  
6142  
6143  
6144  
6145  
6146  
6147  
6148  
6149  
6150  
6151  
6152  
6153  
6154  
6155  
6156  
6157  
6158  
6159  
6160  
6161  
6162  
6163  
6164  
6165  
6166  
6167  
6168  
6169  
6170  
6171  
6172  
6173  
6174  
6175  
6176  
6177  
6178  
6179  
6180  
6181  
6182  
6183  
6184  
6185  
6186  
6187  
6188  
6189  
6190  
6191  
6192  
6193  
6194  
6195  
6196  
6197  
6198  
6199  
6200  
6201  
6202  
6203  
6204  
6205  
6206  
6207  
6208  
6209  
6210  
6211  
6212  
6213  
6214  
6215  
6216  
6217  
6218  
6219  
6220  
6221  
6222  
6223  
6224  
6225  
6226  
6227  
6228  
6229  
6230  
6231  
6232  
6233  
6234  
6235  
6236  
6237  
6238  
6239  
6240  
6241  
6242  
6243  
6244  
6245  
6246  
6247  
6248  
6249  
6250  
6251  
6252  
6253  
6254  
6255  
6256  
6257  
6258  
6259  
6260  
6261  
6262  
6263  
6264  
6265  
6266  
6267  
6268  
6269  
6270  
6271  
6272  
6273  
6274  
6275  
6276  
6277  
6278  
6279  
6280  
6281  
6282  
6283  
6284  
6285  
6286  
6287  
6288  
6289  
6290  
6291  
6292  
6293  
6294  
6295  
6296  
6297  
6298  
6299  
6300  
6301  
6302  
6303  
6304  
6305  
6306  
6307  
6308  
6309  
6310  
6311  
6312  
6313  
6314  
6315  
6316  
6317  
6318  
6319  
6320  
6321  
6322  
6323  
6324  
6325  
6326  
6327  
6328  
6329  
6330  
6331  
6332  
6333  
6334  
6335  
6336  
6337  
6338  
6339  
6340  
6341  
6342  
6343  
6344  
6345  
6346  
6347  
6348  
6349  
6350  
6351  
6352  
6353  
6354  
6355  
6356  
6357  
6358  
6359  
6360  
6361  
6362  
6363  
6364  
6365  
6366  
6367  
6368  
6369  
6370  
6371  
6372  
6373  
6374  
6375  
6376  
6377  
6378  
6379  
6380  
6381  
6382  
6383  
6384  
6385  
6386  
6387  
6388  
6389  
6390  
6391  
6392  
6393  
6394  
6395  
6396  
6397  
6398  
6399  
6400  
6401  
6402  
6403  
6404  
6405  
6406  
6407  
6408  
6409  
6410  
6411  
6412  
6413  
6414  
6415  
6416  
6417  
6418  
6419  
6420  
6421  
6422  
6423  
6424  
6425  
6426  
6427  
6428  
6429  
6430  
6431  
6432  
6433  
6434  
6435  
6436  
6437  
6438  
6439  
6440  
6441  
6442  
6443  
6444  
6445  
6446  
6447  
6448  
6449  
6450  
6451  
6452  
6453  
6454  
6455  
6456  
6457  
6458  
6459  
6460  
6461  
6462  
6463  
6464  
6465  
6466  
6467  
6468  
6469  
6470  
6471  
6472  
6473  
6474  
6475  
6476  
6477  
6478  
6479  
6480  
6481  
6482  
6483  
6484  
6485  
6486  
6487  
6488  
6489  
6490  
6491  
6492  
6493  
6494  
6495  
6496  
6497  
6498  
6499  
6500  
6501  
6502  
6503  
6504  
6505  
6506  
6507  
6508  
6509  
6510  
6511  
6512  
6513  
6514  
6515  
6516  
6517  
6518  
6519  
6520  
6521  
6522  
6523  
6524  
6525  
6526  
6527  
6528  
6529  
6530  
6531  
6532  
6533  
6534  
6535  
6536  
6537  
6538  
6539  
6540  
6541  
6542  
6543  
6544  
6545  
6546  
6547  
6548  
6549  
6550  
6551  
6552  
6553  
6554  
6555  
6556  
6557  
6558  
6559  
6560  
6561  
6562  
6563  
6564  
6565  
6566  
6567  
6568  
6569  
6570  
6571  
6572  
6573  
6574  
6575  
6576  
6577  
6578  
6579  
6580  
6581  
6582  
6583  
6584  
6585  
6586  
6587  
6588  
6589  
6590  
6591  
6592  
6593  
6594  
6595  
6596  
6597  
6598  
6599  
6600  
6601  
6602  
6603  
6604  
6605  
6606  
6607  
6608  
6609  
6610  
6611  
6612  
6613  
6614  
6615  
6616  
6617  
6618  
6619  
6620  
6621  
6622  
6623  
6624  
6625  
6626  
6627  
6628  
6629  
6630  
6631  
6632  
6633  
6634  
6635  
6636  
6637  
6638  
6639  
6640  
6641  
6642  
6643  
6644  
6645  
6646  
6647  
6648  
6649  
6650  
6651  
6652  
6653  
6654  
6655  
6656  
6657  
6658  
6659  
6660  
6661  
6662  
6663  
6664  
6665  
6666  
6667  
6668  
6669  
6670  
6671  
6672  
6673  
6674  
6675  
6676  
6677  
6678  
6679  
6680  
6681  
6682  
6683  
6684  
6685  
6686  
6687  
6688  
6689  
6690  
6691  
6692  
6693  
6694  
6695  
6696  
6697  
6698  
6699  
6700  
6701  
6702  
6703  
6704  
6705  
6706  
6707  
6708  
6709  
6710  
6711  
6712  
6713  
6714  
6715  
6716  
6717  
6718  
6719  
6720  
6721  
6722  
6723  
6724  
6725  
6726  
6727  
6728  
6729  
6730  
6731  
6732  
6733  
6734  
6735  
6736  
6737  
6738  
6739  
6740  
6741  
6742  
6743  
6744  
6745  
6746  
6747  
6748  
6749  
6750  
6751  
6752  
6753  
6754  
6755  
6756  
6757  
6758  
6759  
6760  
6761  
6762  
6763  
6764  
6765  
6766  
6767  
6768  
6769  
6770  
6771  
6772  
6773  
6774  
6775  
6776  
6777  
6778  
6779  
6780  
6781  
6782  
6783  
6784  
6785  
6786  
6787  
6788  
6789  
6790  
6791  
6792  
6793  
6794  
6795  
6796  
6797  
6798  
6799  
6800  
6801  
6802  
6803  
6804  
6805  
6806  
6807  
6808  
6809  
6810  
6811  
6812  
6813  
6814  
6815  
6816  
6817  
6818  
6819  
6820  
6821  
6822  
6823  
6824  
6825  
6826  
6827  
6828  
6829  
6830  
6831  
6832  
6833  
6834  
6835  
6836  
6837  
6838  
6839  
6840  
6841  
6842  
6843  
6844  
6845  
6846  
6847  
6848  
6849  
6850  
6851  
6852  
6853  
6854  
6855  
6856  
6857  
6858  
6859  
6860  
6861  
6862  
6863  
6864  
6865  
6866  
6867  
6868  
6869  
6870  
6871  
6872  
6873  
6874  
6875  
6876  
6877  
6878  
6879  
6880  
6881  
6882  
6883  
6884  
6885  
6886  
6887  
6888  
6889  
6890  
6891  
6892  
6893  
6894  
6895  
6896  
6897  
6898  
6899  
6900  
6901  
6902  
6903  
6904  
6905  
6906  
6907  
6908  
6909  
6910  
6911  
6912  
6913  
6914  
6915  
6916  
6917  
6918  
6919  
6920  
6921  
6922  
6923  
6924  
6925  
6926  
6927  
6928  
6929  
6930  
6931  
6932  
6933  
6934  
6935  
6936  
6937  
6938  
6939  
6940  
6941  
6942  
6943  
6944  
6945  
6946  
6947  
6948  
6949  
6950  
6951  
6952  
6953  
6954  
6955  
6956  
6957  
6958  
6959  
6960  
6961  
6962  
6963  
6964  
6965  
6966  
6967  
6968  
6969  
6970  
6971  
6972  
6973  
6974  
6975  
6976  
6977  
6978  
6979  
6980  
6981  
6982  
6983  
6984  
6985  
6986  
6987  
6988  
6989  
6990  
6991  
6992  
6993  
6994  
6995  
6996  
6997  
6998  
6999  
7000  
7001  
7002  
7003  
7004  
7005  
7006  
7007  
7008  
7009  
7010  
7011  
7012  
7013  
7014  
7015  
7016  
7017  
7018  
7019  
7020  
7021  
7022  
7023  
7024  
7025  
7026  
7027  
7028  
7029  
7030  
7031  
7032  
7033  
7034  
7035  
7036  
7037  
7038  
7039  
7040  
7041  
7042  
7043  
7044  
7045  
7046  
7047  
7048  
7049  
7050  
7051  
7052  
7053  
7054  
7055  
7056  
7057  
7058  
7059  
7060  
7061  
7062  
7063  
7064  
7065  
7066  
7067  
7068  
7069  
7070  
7071  
7072  
7073  
7074  
7075  
7076  
7077  
7078  
7079  
7080  
7081  
7082  
7083  
7084  
7085  
7086  
7087  
7088  
7089  
7090  
7091  
7092  
7093  
7094  
7095  
7096  
7097  
7098  
7099  
7100  
7101  
7102  
7103  
7104  
7105  
7106  
7107  
7108  
7109  
7110  
7111  
7112  
7113  
7114  
7115  
7116  
7117  
7118  
7119  
7120  
7121  
7122  
7123  
7124  
7125  
7126  
7127  
7128  
7129  
7130  
7131  
7132  
7133  
7134  
7135  
7136  
7137  
7138  
7139  
7140  
7141  
7142  
7143  
7144  
7145  
7146  
7147  
7148  
7149  
7150  
7151  
7152  
7153  
7154  
7155  
7156  
7157  
7158  
7159  
7160  
7161  
7162  
7163  
7164  
7165  
7166  
7167  
7168  
7169  
7170  
7171  
7172  
7173  
7174  
7175  
7176  
7177  
7178  
7179  
7180  
7181  
7182  
7183  
7184  
7185  
7186  
7187  
7188  
7189  
7190  
7191  
7192  
7193  
7194  
7195  
7196  
7197  
7198  
7199  
7200  
7201  
7202  
7203  
7204  
7205  
7206  
7207  
7208  
7209  
7210  
7211  
7212  
7213  
7214  
7215  
7216  
7217  
7218  
7219  
7220  
7221  
7222  
7223  
7224  
7225  
7226  
7227  
7228  
7229  
7230  
7231  
7232  
7233  
7234  
7235  
7236  
7237  
7238  
7239  
7240  
7241  
7242  
7243  
7244  
7245  
7246  
7247  
7248  
7249  
7250  
7251  
7252  
7253  
7254  
7255  
7256  
7257  
7258  
7259  
7260  
7261  
7262  
7263  
7264  
7265  
7266  
7267  
7268  
7269  
7270  
7271  
7272  
7273  
7274  
7275  
7276  
7277  
7278  
7279  
7280  
7281  
7282  
7283  
7284  
7285  
7286  
7287  
7288  
7289  
7290  
7291  
7292  
7293  
7294  
7295  
7296  
7297  
7298  
7299  
7300  
7301  
7302  
7303  
7304  
7305  
7306  
7307  
7308  
7309  
7310  
7311  
7312  
7313  
7314  
7315  
7316  
7317  
7318  
7319  
7320  
7321  
7322  
7323  
7324  
7325  
7326  
7327  
7328  
7329  
7330  
7331  
7332  
7333  
7334  
7335  
7336  
7337  
7338  
7339  
7340  
7341  
7342  
7343  
7344  
7345  
7346  
7347  
7348  
7349  
7350  
7351  
7352  
7353  
7354  
7355  
7356  
7357  
7358  
7359  
7360  
7361  
7362  
7363  
7364  
7365  
7366  
7367  
7368  
7369  
7370  
7371  
7372  
7373  
7374  
7375  
7376  
7377  
7378  
7379  
7380  
7381  
7382  
7383  
7384  
7385  
7386  
7387  
7388  
7389  
7390  
7391  
7392  
7393  
7394  
7395  
7396  
7397  
7398  
7399  
7400  
7401  
7402  
7403  
7404  
7405  
7406  
7407  
7408  
7409  
7410  
7411  
7412  
7413  
7414  
7415  
7416  
7417  
7418  
7419

2009-02-10 10:29:00

[0074] The pattern from the resist structure may then be transferred to the material of the underlying substrate. In coated or bilayer photoresists, this will involve transferring the pattern through and coating that may be present and through the underlayer onto the base layer. In single layer photoresists the transfer will be made directly to the substrate. Typically, the pattern is transferred by etching with reactive ions such as oxygen, plasma, and/or oxygen/sulfur dioxide plasma. Suitable plasma tools include, but are not limited to, electron cyclotron resonance (ECR), helicon, inductively coupled plasma, (ICP) and transmission-coupled plasma (TCP) system. Etching techniques are well known in the art and one skilled in the art will be familiar with the various commercially available etching equipment.

[0075] Thus, the compositions of the invention and resulting resist structures can be used to create patterned material layer structures such as metal wiring lines, holes for contacts or vias, insulation sections (e.g., damascene trenches or shallow trench isolation), trenches for capacitor structures, etc. as might be used in the design of integrated circuit devices.

[0076] Accordingly, the processes for making these features involves, after development with a suitable developer as above, etching the layer(s) underlying the resist layer at spaces in the pattern whereby a patterned material layer or substrate section is formed, and removing any remaining resist from the substrate. In some single layer instances, a hard mask may be used below the

resist layer to facilitate transfer of the pattern to a further underlying material layer or section. In the manufacture of integrated circuits, circuit patterns can be formed in the exposed areas after resist development by coating the substrate with a conductive material, e.g., a metallic material, using known techniques such as evaporation, sputtering, plating, chemical vapor deposition, or laser-induced deposition. Dielectric materials may also be deposited by similar means during the process of making circuits. Inorganic ions such as boron, phosphorous, or arsenic can be implanted in the substrate in the process for making p-doped or n-doped circuit transistors. Examples of such processes are disclosed in U.S. Patent Nos. 4,855,017, 5,362,663, 5,429,710, 5,562,801, 5,618,751, 5,744,376, 5,801,094, and 5,821,469. Other examples of pattern transfer processes are described in Chapters 12 and 13 of Moreau, *Semiconductor Lithography, Principles, Practices, and Materials* (Plenum Press, 1988). It should be understood that the invention is not limited to any specific lithographic technique or device structure.

[0077] It is to be understood that, while the invention has been described in conjunction with the preferred specific embodiments thereof, the foregoing description as well as the examples which follow are intended to illustrate and not limit the scope of the invention. Other aspects, advantages and modifications within the scope of the invention will be apparent to those skilled in the art to which the invention pertains.

[0078] All patents, patent applications, and publications mentioned herein are hereby incorporated by reference in their entirety.

**EXPERIMENTAL:**

[0079] The following examples are put forth so as to provide those of ordinary skill in the art with a complete disclosure and description of how to prepare and use the compositions disclosed and claimed herein. Efforts have been made to ensure accuracy with respect to numbers (e.g., amounts, temperature, etc.) but some errors and deviations should be accounted for. Unless indicated otherwise, parts are parts by weight, temperature is in °C and pressure is at or near atmospheric. Additionally, all starting materials were obtained commercially or synthesized using known procedures. Measurements: NMR spectra were recorded on Varian T- 60 (<sup>1</sup>H), Varian CFT-20 (<sup>1</sup>H and <sup>13</sup>C), IBM NR-80 (<sup>19</sup>F) and Bruker AF250 (<sup>1</sup>H and <sup>13</sup>C) spectrometers. Gel permeation chromatography (GPC) was performed with a Waters Model 150 chromatograph equipped with six μ-Styragel columns. Measurements were made at 30°C and 40°C in THF (PMTFMA and copolymers). Combustion analyses were performed by Childers Laboratories, Milford, N.J., and by Chemical Analytical Services, University of California, Berkeley, Calif.

## EXAMPLE 1

### **SYNTHESIS OF POLY(2-HYDROXY-3,3,3-TRIFLUOROPROPYLSILSESQUIOXANE):**

#### **A. SYNTHESIS OF 2-ACETOXY-3,3,3-TRIFLUOROPROPYLTRICHLOROSILANE:**

[0080] 1-(Trifluoromethyl)ethenyl acetate (Aldrich, 188.0 grams, 1.22 mole), trichlorosilane (80.6 grams, 0.60 mole), and 200 ml heptane were placed in a round bottom flask equipped with a water condenser and nitrogen inlet. Platinum(O)-1,3-divinyl-1,1,3,3-tetramethyldisiloxane complex in xylene (10 ml) was added to this solution and heated to reflux for 18 hours.

Afterwards, the solution was cooled to room temperature and additional portions of trichlorosilane (80.6 grams, 0.60 mole) and platinum complex (5 ml) were added and heated to reflux for 48 hours. Proton NMR of the solution indicated about 75 % conversion. A third portion of trichlorosilane (67.7 grams, 0.50 mole) and platinum complex (5 ml) were then added and the solution heated to reflux for 48 hours. Solvents were distilled off at atmospheric pressure and the residue was fractionally distilled under reduced pressure. 2-Acetoxy-3,3,3-trifluoropropyltrichlorosilane (251.7 grams) (1.A) was collected between 100-125°C at 20 mm pressure as a clear liquid.

#### **B. HYDROLYSIS OF 2-ACETOXY-3,3,3-TRIFLUOROPROPYLTRICHLOROSILANE:**

[0081] 2-Acetoxy-3,3,3-trifluoropropyltrichlorosilane (29 grams, 0.1 mole) in tetrahydrofuran (THF, 30 ml) was added dropwise into a cold solution (ice/water bath) of diethylamine (24.1 grams, 0.33 mole) and water (30 ml). The mixture was stirred at room temperature for 1 hour.



The mixture was then diluted with ether (100 ml) and the organic phase separated. The water phase was extracted with ether (2X25 ml) and the organic solutions were combined. The combined organic solution was washed with brine (150 ml) and dried over anhydrous magnesium sulfate. The solvent was removed by rotary evaporation and the product dried under vacuum (19.0 grams).

*Sub A 2e*  
100792289-021002  
**C. SYNTHESIS OF POLY( 2-ACETOXY-3,3,3- TRIFLUOROPROPYLSILSESQUIOXANE):**

[0082] The product from step 1.B was dissolved in toluene (19 grams) and placed in a round bottom flask equipped with a Dean-Stark water separator (to remove the water produced during condensation-reaction) and a water condenser. To this solution, potassium hydroxide (38 mg) was added and the mixture was heated for 18 hours. Afterwards, the solution was filtered through a frit funnel and the solvent was removed in a rotary evaporator. The polymer was then dried under vacuum (16.5 grams).

*Sub A 2e*  
[0083]  
**D. SYNTHESIS OF POLY(2-HYDROXY-3,3,3- TRIFLUOROPROPYLSILSESQUIOXANE):**

[0083] Methanol (50 ml) and ammonium hydroxide (30% solution in water, 11 ml) were added to the polymer product of step 1.C and the resultant solution heated to mild reflux for 1 hour. The solution was then cooled to room temperature and added dropwise into a mixture of water (735 ml) and concentrated hydrochloric acid (15 ml). The resultant precipitated polymer (coagulated) was separated by decantation, rinsed with water (2X1 00 ml) and dried in a vacuum

Sub  
A26  
oven at 80°C for two hours. This polymer was then powdered, transferred into a frit funnel and washed with water (3X100 ml). Then it was dried in a vacuum oven at 80 C for 24 hours. Yield: 8.5 grams, Mw 3,500. Optical Density (OD) of this polymer as thin film is 0.6/micrometer.

EXAMPLE 2

Sub  
A27  
10079283 03199  
20061201 55252001  
POLY(2-HYDROXY-3,3,3-TRIFLUOROPROPYLSILSESQUIOXANE-CO-  
5-(2-TRIMETHYLSILYLETHOXYCARBONYL)NORBONYLSILSESQUIOXANE)(90:10):

A. SYNTHESIS OF 5-(2- TRIMETHYLSILYLETHOXYCARBONYL)NORBONYLTRICHLOROSILANE :

[0084] 2-Trimethylsilylethyl 5-norbornene-2-carboxylate (synthesized using known procedures described in U.S. Patent No, 5,985,524 to Allen et al., 23.8 grams, 0.1 mole) and trichlorosilane (10.8 grams, 0.08 mole) were placed in a round bottom flask equipped with a water condenser and nitrogen inlet. The contents were cooled in ice/water bath and platinum(O)-1,3-divinyl-1,1,3,3- tetramethyl disiloxane complex in xylene (100 ml) was added and stirred. After two hours, the bath was removed and the contents stirred at room temperature for 18 hours. Proton NMR spectrum of the mixture indicated only 50% conversion. The contents were again cooled in the water ice bath and trichlorosilane (6.8 grams, 0.05 mole) and platinum(O)-1,3- divinyl-1,1,3,3- tetramethydisiloxane complex in xylene (100 ml) were added and stirred. After two hours, the bath was removed and the contents stirred at room temperature for 18 hours. Afterwards, the volatiles were removed under vacuum. The colorless liquid thus obtained contained 92% of the desired product 5-(2- trimethylsilylethoxycarbonyl)

Sub  
A, 27  
cont

norbonyltrichlorosilane(2.A) and 8% of the starting material, 2-trimethylsilylethyl 5-norbornene-2-carboxylate. As the starting material would not react in the next step of the reaction, further purification was not necessary.

Sub  
A, 28

**B. HYDROLYSIS OF THE MONOMER MIXTURES :**

10079229-021002

[0085] 2-Acetoxy-3,3,3-trifluoropropyltrichlorosilane (1.A above) and 5-(2-trimethylsilylethoxycarbonyl) norbonyltrichlorosilane were mixed together in a molar ratio of 90:10 and hydrolyzed as described in 1.B above.

**C. SYNTHESIS OF POLY(2-ACETOXY-3,3,3- TRIFLUOROPROPYLSILSESQUIOXANE-CO-5-(2-TRIMETHYLSILYLETHOXYCARBONYL)NORBONYLSILSESQUIOXANE)**

[0086] The product from step 2.B was condensed to give the desired polymer as described in step 1.C.

**D. SYNTHESIS OF POLY(2-HYDROXY-3,3,3- TRIFLUOROPROPYLSILSESQUIOXANE-CO-5-(2-TRIMETHYLSILYIETHOXYCARBONYL)NORBONYLSILSESQUIOXANE)**

[0087] The product from step 2.C was reacted with ammonium hydroxide as described in step 1.D and the resulting polymer was precipitated into a water/aceitic acid mixture.

### EXAMPLE 3

**POLY[5-{2-(1',1',1'-TRIFLUORO-2'-TRIFLUOROMETHYL-2'-HYDROXY)} NORBORNYSILSESQUOXANE]:**

**A. 5-[2-(1',1',1'-TRIFLUORO-2'-TRIFLUOROMETHYL-2'-ACETOXY)] NORBORNYLTRICHLOROSILANE:**

[0088] 2-(1',1',1'-Trifluoro-2'-trifluoromethyl-2'-acetoxy)-5- norbornene, (49 grams, 0.155 mole), trichlorosilane (29.4 grams, 0.22 mole), and 200 ml hexane were placed in a round bottom flask equipped with a water condenser and nitrogen inlet. Platinum(0)-1,3-divinyl-1,1,3,3-tetramethyldisiloxane complex in xylene (4 ml) was added to this solution and heated to reflux for 18 hours. The volatiles were then removed by distillation at atmospheric pressure and the residue fractionally distilled under reduced pressure. The product, 5-[2-(1',1',1'-trifluoro-2'-trifluoromethyl-2'-acetoxy)] norbornyltrichlorosilane (60.08 grams) was collected between 130-155 °C at 2 mm pressure as a clear liquid.

**B. HYDROLYSIS OF 5-[2-(1',1',1'-TRIFLUORO-2'-TRIFLUOROMETHYL-2'-ACETOXY)]:**

**NORBORNYLTRICHLOROSILANE**

[0089] 5-[2-(1',1',1'-Trifluoro-2'-trifluoromethyl-2'-acetoxy)] norbornyltrichlorosilane (32.5 grams, 0.07 mole) in tetrahydrofuran (THF, 30 ml) was added dropwise into a cold solution (ice/water bath) of diethylamine (17.34 grams, 0.24 mole) and water (30 ml). The mixture was stirred at room temperature for 1 hour and then diluted with ether (100 ml). The organic phase was separated, the water phase extracted with ether (2X100 ml) and the organic solutions were combined. This combined organic solution was washed with brine (150 ml) and

dried over anhydrous magnesium sulfate. The solvent was then removed in a rotary evaporator and the product, 5-[2-(1',1',1'-trifluoro-2'-trifluoromethyl-2'-acetoxy)] norbornyltrichlorosilane, was dried under vacuum (24.2 grams).

**C. SYNTHESIS OF POLY[5-{2-(1',1',1'-TRIFLUORO-2'-TRIFLUOROMETHYL-2'-ACETOXY)}]**

**NORBORNYSILSESQUIOXANE]:**

[0090] The product from step 3.B was dissolved in toluene (25 grams) and placed in a round bottom flask equipped with a Dean-Stark water separator (to remove the water produced during condensation reaction) and a water condenser. To this solution, potassium hydroxide (50 mg) was added and the mixture was heated for 18 hours. Afterwards, the solutions was filtered through a frit funnel and the solvent was removed in a rotary evaporator. The remaining polymer was dried under vacuum (22.4 grams).

**D. SYNTHESIS OF POLY[5-{2-(1',1',1'-TRIFLUORO-2'-TRIFLUOROMETHYL-2'-HYDROXY)}]**

**NORBORNYSILSESQUIOXANE]:**

[0091] The polymer product from step 3.C was mixed with methanol (75 ml) and ammonium hydroxide (30% solution in water, 15 ml) and the resulting solution heated to mild reflux for 9 hours. The solution was cooled to room temperature and added dropwise into a mixture of water (1.5 liter) and concentrated hydrochloric acid (30 ml). The precipitated polymer (coagulated) was separated by decantation, rinsed with water (2X100 ml) and dried in a vacuum oven at 80 C for two hours. This dried precipitate was then powdered, transferred into a frit funnel and washed

with water (3X100 ml) and dried in a vacuum oven at 80 C for 24 hours. Yield: 17.4 grams, Mw = 3,300.

#### EXAMPLE 4

**POLY[2-HYDROXY-3,3,3-TRIFLUOROPROPYLSILSESQUIOXANE-CO- 5-(2-T-BUTOXYCARBONY) NORBONYLSILSESQUIOXANE](80:20):**

##### **A. SYNTHESIS OF 5-(2-T-BUTOXYCARBONYL)NORBONYLTRICHLOROSILANE:**

[0092] Anhydrous hexane (50 ml), t-butyl-5-norbornene-2-carboxylate (9.7 grams, 0.05 mole), and platinum on alumina (5 wt%, 300 mg) were placed in a round bottom flask equipped with a water condenser and nitrogen inlet. Trichlorosilane (13.54 grams, 0.10 mole) was added to this mixture and heated to reflux for 40 hours. Afterwards, the solution was filtered under nitrogen into a flask containing 100 mg of calcium hydride. Solvent and excess trichlorosilane were removed under vacuum. The percentage conversion was estimated by proton NMR and the product was used without further purification.

##### **B. HYDROLYSIS OF THE MONOMER MIXTURES:**

[0093] 2-Acetoxy-3,3,3-trifluoropropyltrichlorosilane and 5-(2-t-butoxycarbonyl) norbonyltrichlorosilane were mixed together in the mole ratio of 80:20 and hydrolyzed as described in 3.B above.

**C. SYNTHESIS OF [2-ACETOXY-3,3,3-TRIFLUOROPROPYLSILSESQUIOXANE-CO-**

**5-(2-T-BUTOXYCARBONY)NORBORNYSILSESQUIOXANE](80:20):**

[0094] The product from step 4.B was condensed to give the desired polymer as described step 3.C.

**D. SYNTHESIS OF [2-HYDROXY-3,3,3-TRIFLUOROPROPYLSILSESQUIOXANE-**

**CO-5-(2-T-BUTOXYCARBONY) NORBORNYSILSESQUIOXANE](80:20):**

[0095] The product from step 4.C was reacted with ammonium hydroxide as described In step 3.D. The polymer was precipitated into water/acetic acid mixture.

**EXAMPLE 5**

**PARTIAL PROTECTION OF POLY(2-HYDROXY-3,3,3-TRIFLUOROPROPYLSILSESQUIOXANE)**

**WITH AN ACID-CLEAVABLE TRIMETHYLSILYL GROUP:**

[0096] Poly(2-Hydroxy-3,3,3- trifluoropropylsilsesquioxane) (1.4 above, 4 grams, 0.024 moles of monomer units) was dissolved in anhydrous tetrahydrofuran (10 ml) and 1,1,1,3,3,3-hexamethyldisilazane (1.94 grams, 0.012 mole) was added to this mixture. The contents were heated to reflux under nitrogen for 2 hours. The partially protected polymer was precipitated into 500 ml deionized water. The precipitate was filtered through a frit funnel and dried under vacuum at 80°C for 24 hours. Yield: 2.3 grams. Protection level: 50 % by NMR.

## **EXAMPLE 6**

### **SYNTHESIS OF THE DI-T-BUTYL GLYCOLATE ACID-LABILE DISSOLUTION INHIBITOR, HEXAFLUOROBISPHENOL:**

[0097] A mixture of hexafluorobisphenol A (20 grams, 0.06 mole), t-butyl bromoacetate (25.6 grams, 0.13 mole), potassium carbonate (19.3 grams, 0.13 mole), and potassium iodide (200 mg) in acetone (200 ml) was stirred at room temperature under nitrogen for 24 hours. Afterwards, the solids were filtered off and the solvent was removed in a rotary evaporator. The residue was dissolved in ether (200 ml) and washed with 2x200 ml deionized water and dried over anhydrous magnesium sulfate. The solvent was removed under vacuum and the residue was recrystallized from hexane (60 ml) to give 24 grams of white crystalline product. M.Pt: 58-59°C.

## **EXAMPLE 7**

### **157 NM POSITIVE BILAYER RESIST:**

[0098] Poly(2-Hydroxy-3,3,3-trifluoropropylsilsesquioxane-co-5-(2-trimethylsilylethoxycarbonyl) norbornylsilsesquioxane)(90:10) (2.0 grams) and di(t-butyl)phenyliodonium perfluorooctane sulfonate (PFOS, 100 mg) were dissolved in propylene glycol monomethyl ether acetate (PGMEA, 16 grams) and filtered through a 0.20 microns syringe filter. Around 500-1000 ppm of a fluorinated surfactant (FC-430/ 3M) was added to improve the film quality.



### **EXAMPLE 8**

#### **POSITIVE BILAYER RESIST FORMULATION WITH AN ACID-LABILE DISSOLUTION INHIBITOR:**

[0099] Poly(2-Hydroxy-3,3,3-trifluoropropylsilsesquioxane) (1.0 gram) hexafluorobisphenol, a di-t-butyl glycolate (Example 4, 200 mg), and di(t-butyl)phenyl iodonium perfluorooctane sulfonate (PFOS, 50 mg) were dissolved in propylene glycol monomethyl ether acetate (PGMEA, 8.5 grams) and filtered through a 0.20 microns syringe filter. Around 500-1000 ppm of a fluorinated surfactant (FC-430/ 3M) was added to improve the film quality.

### **EXAMPLE 9**

#### **POSITIVE BILAYER RESIST FORMULATION WITH A POLYMERIC DISSOLUTION INHIBITOR:**

[0100] Poly(2-Hydroxy-3,3,3-trifluoropropylsilsesquioxane) (2.55 grams), Poly(t-butylmethacrylate) (MW=13,000) (0.45 g), and di(t-butyl)phenyl iodonium perfluorooctane sulfonate (PFOS, 150 mg) were dissolved in propylene glycol monomethyl ether acetate (PGMEA, 27 grams) and filtered through a 0.20 microns syringe filter. Around 500-1000 ppm of a fluorinated surfactant (FC-430/ 3M) was added to improve the film quality.

### **EXAMPLE 10**

#### **157 NM POSITIVE BILAYER RESIST EVALUATION:**

[0101] A silicon substrate was coated with 0.6 microns of an organic underlayer and baked at 2251 °C for 2 minutes. The underlayer was overcoated with 1500 Å of a 157 nm positive bilayer composition (Examples 5 and 6). The films were baked at 1300 °C for 1 minute to drive the solvent out. The films were then imagewise exposed at 157 nm or 193 nm (dose 15 - 100 mJ/cm<sup>2</sup>). The film was then baked at 1300 °C for 1 minute and the top layer was developed with 0.263 N tetramethyl ammonium hydroxide. High resolution images were obtained with this resist.

### **EXAMPLE 11**

#### **157 NM NEGATIVE BILAYER RESIST:**

[0102] Poly(2-Hydroxy-3,3,3-trifluoropropylsilsesquioxane) (1.0 gram), POWDERLINK® (American Cyanamid Company, 80 mg), and di(t-butyl)phenyl iodonium perfluorobutane sulfonate (PFBUS, 40 mg) were dissolved in propylene glycol monomethyl ether acetate (PGMEA, 8 grams) and filtered through a 0.20 microns syringe filter. Around 500-1000 ppm of a fluorinated surfactant (FC-430/ 3M) was added to improve the film quality.

## EXAMPLE 12

### 157 NM NEGATIVE BILAYER RESIST EVALUATION:

[0103] A silicon substrate was coated with 0.6 microns of an organic underlayer and baked at 2250°C for 2 minutes. The underlayer was overcoated with 1500 Å of a 157 nm negative bilayer composition (Example 7). The films were baked at 1300°C for 1 minute to drive the solvent out. The films were then imagewise exposed at 157 nm or 193 nm (dose 15 - 100 mJ/cm<sup>2</sup>). The film was then baked at 1300°C for 1 minute and the top layer was developed with 0.263 N tetramethyl ammonium hydroxide. High resolution negative images were obtained with this resist.

[0104] Although this invention has been described with respect to specific embodiments, the details thereof are not to be construed as limitations, for it will be apparent that various embodiments, changes and modifications may be resorted to without departing from the spirit and scope thereof, and it is understood that such equivalent embodiments are intended to be included within the scope of this invention.

**APPENDIX A -- AMENDMENTS TO THE SPECIFICATION**


Please amend paragraphs 4, 8, 19, 20, 23-26, 33, 35, 41-44, 44, 45, 48, 50, 55-57, 61, 66, 69, 73, 82-85 and 92 as follows:

[0004] In order to overcome these problems, bilayer resists have been developed. Such bilayer resists are generally comprised of a top thin film imaging layer coated on a thick organic underlayer and are patterned by i) imagewise exposure and development of the top layer, and then (ii) anisotropically transferring the developed pattern in the top layer to the thick underlayer and subsequently to the substrate. The top imaging layer contains a suitable ~~refactory~~ refractory oxide precursor such as silicon, boron or germanium that enables the use of oxygen-reactive ion etching (RIE) in the image transfer step.

[0008] Fluorocarbon polymers, such as polymers prepared from trifluoromethyl-substituted acrylates, have been described previously. See, for example, Ito et al. (1981), "Methyl Alpha-Trifluoromethylacrylate, an E- Beam and UV Resist," *IBM Technical Disclosure Bulletin* 24(4):991, Ito et al. (1982) *Macromolecules* 15:915-920, which describes preparation of poly(methyl  ~~$\alpha$ -trifluoromethylacrylate~~  $\alpha$ -trifluoromethylacrylate) and poly( $\alpha$ -trifluoromethylacrylonitrile) from their respective monomers, and Ito et al. (1987), "Anionic Polymerization of  $\alpha$ -(Trifluoromethyl)Acrylate," in *Recent Advances in Anionic Polymerization*, T. E. Hogen-Esch and J. Smid, Eds. (Elsevier Science Publishing Co., Inc.), which describes an anionic polymerization method for preparing polymers of trifluoromethylacrylate. Willson et al., *Polymer Engineering and Science* 23(18):1000-1003, also discuss poly(methyl  $\alpha$ -trifluoromethylacrylate) and the use thereof in a positive electron beam resist.


[0019] In one aspect, then, the present invention relates to a fluorocarbonol and/or fluoroacid functionalized silsesquioxane polymer comprised of monomer units having structure (I)

(I)




Within structure (II), R<sup>1</sup>, R<sup>2</sup>, R<sup>3</sup> and R<sup>4</sup> are independently selected from the group consisting of substituents having structure (II)

(II)



wherein p is 0, 1, or 2, s is 0, 1, or 2, R<sup>7</sup> is hydrogen, alkyl or fluoroalkyl, R<sup>8</sup> is alkyl or fluoroalkyl, R<sup>9</sup> is OH, COOH or an acid-cleavable moiety, and Q is selected from the group consisting of substituted (e.g., fluorinated) and unsubstituted arylene, substituted (e.g., fluorinated) and unsubstituted cycloalkylene, substituted and unsubstituted alkarylene, and moieties having the structure (III)


(III)



wherein R<sup>5</sup> and R<sup>6</sup> are independently hydrogen, alkyl (e.g., linear, branched, or cycloalkyl) or fluoroalkyl and n is an integer from 1 zero to 4. The polymer may serve as either the base-soluble component of an unexposed resist in a negative resist or as an acid-labile material that releases acid following irradiation in a positive resist.

**[0020]** In another aspect of the invention, the present invention relates to a fluorocarbonol and/or fluoroacid functionalized silsesquioxane copolymer comprising monomer units having structure (I), as described above, and monomer units having structure (IV)

(IV)



wherein  $\text{R}^{10}$ ,  $\text{R}^{11}$ ,  $\text{R}^{12}$  and  $\text{R}^{13}$  are independently hydrogen, alkyl (e.g., linear, or branched, or cycloalkyl)-, fluoroalkyl, fluorocarbonol, fluoroacid or an acid-cleavable moiety, with the proviso that at least one of  $\text{R}^{10}$ ,  $\text{R}^{11}$ ,  $\text{R}^{12}$  and  $\text{R}^{13}$  is an acid-cleavable moiety. The copolymer may serve as an acid-labile material that releases acid following irradiation.

**[0023]** The present invention also relates to the use of the resist composition in a lithography method. The process involves the steps of (a) optionally coating a substrate with an organic underlayer; (b) coating the organic underlayer with a top layer comprising: i) a radiation sensitive acid generator and ii) a fluorocarbonol functionalized silsesquioxane polymer containing polar groups and acid-labile groups; (b) exposing the top layer selectively to a predetermined pattern of radiation to form a latent image therein; (c) developing the image in the top layer using a suitable developer composition; and (e) transferring the image to the substrate. The resist composition may be used to form a single layer photoresist or a bilayer photoresist. The radiation may be ultraviolet, electron beam or x-ray. Ultraviolet radiation is preferred, particularly deep ultraviolet radiation having a wavelength of less than about 250 nm, e.g., 157 nm, 193 nm, or 248 nm. The pattern from the resist structure may then be transferred to the underlying substrate.

~~**[0024]** The radiation may be ultraviolet, electron beam or x-ray. Ultraviolet radiation is preferred, particularly deep ultraviolet radiation having a wavelength of less than about 250 nm, e.g., 157 nm, 193 nm, or 248 nm. The pattern from the resist structure may then be transferred to the underlying substrate. Typically, the transfer is achieved by reactive ion etching or some other etching technique. Thus, the compositions of the invention and resulting resist structures~~

can be used to create patterned material layer structures such as metal wiring lines, holes for contacts or vias, insulation sections (e.g., damascene trenches or shallow trench isolation), trenches for capacitor structures; etc., as might be used in the design of integrated circuit devices.

[0025] Fig. 1 ~~presents~~ is a graph illustrating the optical density of a polymer of the invention at a range of UV wavelengths.

[0026] Fig. 2 ~~presents copolymer~~ illustrates a polymer of the inventions ~~with acid-cleavable invention~~ substituted with fluorocarbonol pendent groups.


[0033] The term "fluorinated" refers to replacement of a hydrogen atom in a molecule or molecular segment with a fluorine atom. The term "fluoroalkyl" refers to an alkyl group wherein at least one hydrogen atom has been replaced with a fluorine atom and includes, for example, trifluoromethyl, difluoromethyl, 2,2,2-trifluoroethyl, pentafluoromethyl, 3,3,3-trifluoromethyl, etc. Similarly, the term "~~fluorocarbonol~~ fluorocarbonol" refers to an alcohol moiety in which at least one of the hydrogens bonded to a carbon atom has been replaced with a fluorine atom and includes, for example,  $-\text{CF}_2\text{OH}$ ,  $-\text{CH}(\text{CF}_3)\text{-OH}$ ,  $-\text{C}(\text{CF}_3)_2\text{-OH}$ ,  $-\text{CH}_2\text{CF}_2\text{OH}$ , etc. The term "fluoroacid" refers to a carboxylic acid substituent in which at least one of the hydrogens bonded to a carbon atom has been replaced with a fluorine atom and includes, for example,  $-\text{CF}_2\text{COOH}$ ,  $-\text{CH}(\text{CF}_3)\text{-COOH}$ ,  $-\text{C}(\text{CF}_3)_2\text{-COOH}$ ,  $-\text{CH}_2\text{CF}_2\text{COOH}$ , etc. The term "perfluorinated" is also used in its conventional sense to refer to a molecule or molecular segment wherein all hydrogen atoms are replaced with fluorine atoms. Unless otherwise indicated, "fluorinated" substituents (such as fluoralkyl and the like) include perfluorinated substituents.

[0035] The terms "aralkyl" and "alkaryl" refer to moieties containing both alkyl and aryl species, typically containing less than about 24 carbon atoms, and more typically less than about 12 carbon atoms in the alkyl segment of the moiety, and typically containing 1 to 5 aromatic rings. The rings may be either unsubstituted or substituted with 1 or more substituents typically


selected from the group consisting of halogen, ~~haloalkyl~~ haloalkyl, alkyl, alkenyl, alkynyl, alkoxy, alkenyloxy, alkynyloxy, alkylthio, aryl, aralkyl, and the like. The term "aralkyl" refers to aryl-substituted alkyl groups, while the term "alkaryl" refers to alkyl-substituted aryl groups. The terms "aralkylene" and "alkarylene" are used in a similar manner to refer to aryl-substituted alkylene and alkyl-substituted arylene moieties.

**THE FLUOROCARBINOL- AND/OR FLUOROACID-FUNCTIONALIZED SILSESQUIOXANE POLYMERS**  
**THE FLUOROCARBINOL- AND/OR FLUOROACID-FUNCTIONALIZED SILSESQUIOXANE**  
**POLYMERS:**

[0041] The fluorocarinol- and/or fluoroacid-functionalized silsesquioxane polymer comprised of a monomer unit having structure (I)




Within structure (I),  $R^1$ ,  $R^2$ ,  $R^3$  and  $R^4$  are independently selected from the group consisting of substituents having structure (II)



wherein  $p$  is 0, 1, or 2,  $s$  is 0, 1, or 2,  $R^7$  is hydrogen, linear or branched alkyl, or fluoroalkyl,  $R^8$  is fluoroalkyl,  $R^9$  is OH, COOH or an acid-cleavable moiety, and  $Q$  is selected from the group consisting of substituted and unsubstituted arylene, substituted and unsubstituted cycloalkylene, substituted and unsubstituted alkarylene, and moieties having the structure (III)



(III)



wherein  $R^5$  and  $R^6$  are independently hydrogen, alkyl (e.g., linear, branched, or cycloalkyl) or fluoroalkyl and  $n$  is an integer from ~~1~~ zero to 4.

[0042] Preferred  $R^5$  and  $R^6$  substituents are hydrogen,  $C_1$ - $C_6$  alkyl and  $C_1$ - $C_6$  fluoroalkyl. Most preferred  $R^5$  and  $R^6$  substituents are hydrogen, methyl, ethyl and trifluoromethyl-substituted  $C_1$ - $C_6$  alkyl, such as trifluoromethyl, ~~2,2,2-trifluoroethyl~~ 2,2,2-trifluoroethyl, and ~~3,3,3-trifluoromethyl~~ 3,3,3-trifluoropropyl.


[0043] Preferred  $R^7$  substituents are hydrogen,  $C_1$ - $C_6$  alkyl and  $C_1$ - $C_6$  fluoroalkyl. Most preferred  $R^7$  substituents are hydrogen, methyl, ethyl and ~~trifluoromethyl-substituted~~ trifluoromethyl-substituted  $C_1$ - $C_6$  alkyl, such as trifluoromethyl, 2,2,2-trifluoroethyl, and ~~3,3,3-trifluoromethyl~~ 3,3,3-trifluoropropyl.


[0044] Preferred  $R^8$  substituents are  ~~$C_1$ - $C_6$  alkyl and~~  $C_1$ - $C_6$  fluoroalkyl. Most preferred  $R^8$  substituents are ~~methyl, ethyl and trifluoromethyl-substituted~~ trifluoromethyl-substituted  $C_1$ - $C_6$  alkyl, such as trifluoromethyl, 2,2,2-trifluoroethyl, and ~~3,3,3-trifluoromethyl~~ 3,3,3-trifluoropropyl.

[0045] In the structure (II) substituent, ~~the~~  $R^9$  moiety is -OH, -COOH, or an acid-cleavable moiety, i.e., a molecular moiety that is cleavable with acid, particularly photogenerated acid. Suitable acid-cleavable functionalities include, but are not limited to, esters of the formula  $-(L)_v-$  (CO)-OR<sup>14</sup>, carbonates of the formula  $-(L)_v-O-(CO)-O-R^{15}$ , and ethers of the formula -OR<sup>16</sup>, wherein R<sup>14</sup>, R<sup>15</sup> and R<sup>16</sup> are selected so as to render the functionality acid-cleavable,  $v$  is zero or 1, and L is a linking group such as an alkylene group (e.g., linear, branched or cycloalkylene group such as norbornyl or cyclohexylene) a fluoroalkylene group, or an aryl group. In acid-cleavable ester groups, i.e., substituents having the formula  $-(L)_v-(CO)-OR^{14}$ , R<sup>14</sup> is preferably

either a tertiary alkyl, e.g., *t*-butyl, a cyclic or alicyclic substituent (generally C<sub>7</sub>-C<sub>12</sub>) with a tertiary attachment point such as adamantyl, norbornyl, isobornyl, 2-methyl-2-adamantyl, 2-methyl-2-isobornyl, 2-butyl-2-adamantyl, 2-propyl-2-isobornyl, 2-methyl-2-tetracyclododecenyl, 2-methyl-2-dihydrodicyclopentadienyl-cyclohexyl, 1-methylcyclopentyl or 1-methylcyclohexyl, or a 2-trialkylsilylethyl group, such as 2-trimethylsilylethyl, or 2-triethylsilylethyl.

[0048] ~~Example~~ Examples of substituents having structure (II) include, but are not limited to,





[0050] The polymer and copolymer may comprise different monomer units each having structure (I), and, in the case of the copolymer, different monomer units each having structure (IV). The polymer and copolymer may also comprise one or more other monomer units, typically formed from addition polymerizable monomers, preferably vinyl monomers, for example, to enhance the performance of the photoresist. Thus, the polymer and copolymer may comprise minor amounts of acrylic acid or methacrylic acid monomer (e.g., 5-30%) to enhance development.

[0055] Other useful acid generators include the family of nitrobenzyl esters and the s-triazine derivatives. Suitable s-triazine acid generators are disclosed, for example, in U.S. Patent No. 4,189,323. \_\_\_\_\_




Still other suitable acid generators include N-camphorsulfonyloxynaphthalimide, N-pentafluorophenylsulfonyloxynaphthalimide, ionic iodonium sulfonates, e.g., diaryl iodonium (alkyl or aryl) sulfonate and bis-(di-*t*-butylphenyl)iodonium camphanylsulfonate, perfluoroalkanesulfonates, such as perfluoropentanesulfonate, perfluorooctanesulfonate, perfluoromethanesulfonate; aryl (e.g., phenyl or benzyl) triflates and derivatives and analogs thereof, e.g., triphenylsulfonium triflate or bis-(*t*-butylphenyl)iodonium triflate; pyrogallol derivatives (e.g., trimesylate of pyrogallol); trifluoromethanesulfonate esters of hydroxyimides,  $\alpha$ ,  $\alpha'$ -bis-sulfonyl-diazomethanes; sulfonate esters of nitro-substituted benzyl alcohols; naphthoquinone-4-diazides; and alkyl disulfones. Other suitable photoacid generators are disclosed in Reichmanis et al. (1991), *Chemistry of Materials* 3:395, and in U.S. Patent No. 5,679,495 to Yamachika et al. Additional suitable acid generators useful in conjunction with the compositions and methods of the invention will be known to those skilled in the art and/or are described in the pertinent literature.

[0056] The photoresist composition herein comprises both a fluorocarbonol- and/or fluoroacid-functionalized silsesquioxane polymer or copolymer as described in detail above, and an acid generator, with the polymer or copolymer representing up to about 99.5 wt.% of the solids included in the composition, and the photoacid generator representing approximately 0.5-10 wt.% of the solids contained in the composition. The photoresist may take the form of a negative or a positive photoresist and other components and additives may also be present.

[0057] If the photoresist is a positive photoresist, the composition may include a monomeric or polymeric acid-cleavable dissolution inhibitor. When the resist-coated substrate is patternwise exposed to a radiation source, the acid generated by the radiation-sensitive acid generator will cleave the acid-cleavable moieties in the polymer or copolymer and/or in the dissolution inhibitor, thus making the exposed areas of the photoresist composition soluble in conventional developer solutions. If included, the dissolution inhibitor, may be present either as a pendent moiety on the polymer or copolymer chain, as an additional element in the photoresist composition, or as a combination of the two. If a dissolution inhibitor is present, it will typically represent in the range of about 1 wt.% to 40 wt.%, preferably about 5 wt.% to 30 wt.%, of the total solids. Positive photoresist compositions that comprise a dissolution inhibitor need not have acid-cleavable moieties on the silsesquioxane polymer, i.e. R<sup>9</sup> need not be an acid-labile group, as the dissolution inhibitor will independently be sufficient to result in the dissolution of the exposed areas of resist.

[0061] The crosslinking agent may be any suitable crosslinking agent known in the negative photoresist art that is otherwise compatible with the other components of the photoresist composition. The crosslinking agent preferably acts to crosslink the polymer component in the presence of a generated acid. Preferred crosslinking agents are glycoluril compounds such as tetramethoxymethyl glycoluril, \_\_\_\_\_, methylpropyltetramethoxymethyl glycoluril, and methylphenyltetramethoxymethyl glycoluril, available under the POWDERLINK<sup>(R)</sup> trademark from American Cyanamid Company. Other

possible crosslinking agents include, but are not limited to: 2,6-bis(hydroxymethyl)-p-cresol and compounds having the following structures:



including their analogs and derivatives, such as those found in Japanese Laid-Open Patent Application (Kokai) No. 1-293339, as well as etherified amino resins, for example, methylated or butylated melamine resins (N-methoxymethyl- or N-butoxymethyl-melamine respectively) or methylated/butylated glycolurils, for example as can be found in Canadian Patent No. 1 204 547. Combinations of crosslinking agents may be used. The remainder of the composition is composed of a solvent and may additionally, if necessary or desirable, include customary additives such as dyes, sensitizers, additives used as stabilizers and acid-diffusion controlling agents, coating aids such as surfactants or anti-foaming agents, adhesion promoters and plasticizers.

[0061] [second instance; paragraph misnumbered] ~~The remainder of the composition is composed of a solvent and may additionally, if necessary or desirable, include customary additives such as dyes, sensitizers, additives used as stabilizers and acid-diffusion controlling agents, coating aids such as surfactants or anti-foaming agents, adhesion promoters and plasticizers.~~

[0066] Surfactants may be used to improve coating uniformity, and include a wide variety of ionic and non-ionic, monomeric, oligomeric, and polymeric species. Likewise, a wide variety of anti-foaming agents may be employed to suppress coating defects. Adhesion promoters may be used as well; again, a wide variety of compounds may be employed to serve this function. A wide variety of monomeric, oligomeric, and polymeric plasticizers such as oligo- and ~~polyethyleneglycol~~ polyethylene glycol ethers, cycloaliphatic esters, and non-acid reactive ~~steroidally derived~~ steroidally derived materials may be used as plasticizers, if desired.

[0069] The present invention also relates to a process for generating a resist image on a substrate comprising the steps of: (a) coating a substrate with a film comprising the resist composition of the present invention; (b) imagewise exposing the film to radiation; and (c) developing the image. The first step involves coating the substrate with a film comprising the resist composition dissolved in a suitable solvent. Suitable substrates are ceramic, metallic or semiconductive, and preferred substrates are silicon-containing, including, for example, silicon dioxide, silicon nitride, and silicon oxynitride. The substrate may or may not be coated with an organic anti-reflective layer prior to deposition of the resist composition. Alternatively, a bilayer substrate may be employed wherein a resist composition of the invention forms an upper resist layer (i.e., the imaging layer) on top of a bilayer substrate comprised of a base layer and underlayer that lies between the upper resist layer and the base layer. The base layer of the bilayer substrate is comprised of a suitable substrate material, and the underlayer of the bilayer substrate is comprised of a material that is highly absorbing at the imaging wavelength and compatible with the imaging layer. Conventional underlayers include cross-linked poly(hydroxystyrene), polyesters, polyacrylates, fluorinated polymers, ~~cyclic-olefin~~ cyclic olefin polymers and the like, including diazonaphthoquinone (DNQ)/novolak resist material.

[0073] The third step involves development of the image with a suitable solvent. Suitable solvents include an aqueous base, preferably an aqueous base without metal ions such as the industry standard developer tetramethylammonium hydroxide or choline. In positive photoresist applications, the exposed areas of the photoresist will be soluble, leaving behind the unexposed areas. In negative photoresist applications, the converse is true, i.e., the unexposed regions will be soluble to the developer while the exposed regions will remain. Because the fluorocarbonol- and/or fluoroacid-functionalized silsesquioxane monomer of the photoresist composition is substantially transparent at 157 nm, the resist composition is uniquely suitable for use at that wavelength. However, as stated before, the resist may also be used with wavelengths of 193 nm, 248 nm, 254 nm and 365 nm, or with electro beam or x-ray radiation.

**C. SYNTHESIS OF ~~POLY(2-ACETOXY-3,3,3-TRIFLUOROPROPYLSILSESQUIOXANE)~~ POLY(2-ACETOXY-3,3,3-TRIFLUOROPROPYLSILSESQUIOXANE):**

[0082] The product from step 1.B was dissolved in toluene (19 grams) and placed in a round bottom flask equipped with a Dean-Stark water separator (to remove the water produced during condensation-reaction) and a water condenser. To this solution, potassium hydroxide (38 mg) was added and the mixture was heated for 18 hours. Afterwards, the solution was filtered through a frit funnel and the solvent was removed in a rotary evaporator. The polymer was then dried under vacuum (16.5 grams).

**D. SYNTHESIS OF ~~POLY(2-HYDROXY-3,3,3-TRIFLUOROPROPYLSILSESQUIOXANE)~~ POLY(2-HYDROXY-3,3,3-TRIFLUOROPROPYLSILSESQUIOXANE):**

[0083] Methanol (50 ml) and ammonium hydroxide (30% solution in water, 11 ml) were added to the polymer product of step 1.C and the resultant solution heated to mild reflux for 1 hour. The solution was then cooled to room temperature and added dropwise into a mixture of water (735 ml) and concentrated hydrochloric acid (15 ml). The resultant precipitated polymer (coagulated) was separated by decantation, rinsed with water (~~2X100~~ 2X100 ml) and dried in a vacuum oven at 80 °C for two hours. This polymer was then powdered, transferred into a frit funnel and washed with water (3X100 ml). Then it was dried in a vacuum oven at 80 °C for 24

hours. Yield: 8.5 grams, Mw 3,500. Optical Density (OD) of this polymer as thin film is 0.6/micrometer.

## EXAMPLE 2

**POLY(2-HYDROXY-3,3,3-TRIFLUOROPROPYLSILSESQUIOXANE-CO-5-(2-TRIMETHYLSILYLETHOXYCARBONYL)NORBORNYSILSESQUIOXANE)(90:10):**

**A. SYNTHESIS OF 5-(2-TRIMETHYLSILYLETHOXYCARBONYL)NORBONYLTRICHLOROSILANE:**

**POLY(2-HYDROXY-3,3,3-TRIFLUOROPROPYLSILSESQUIOXANE-CO-5-(2-TRIMETHYLSILYLETHOXYCARBONYL)NORBORNYSILSESQUIOXANE)(90:10):**

**A. SYNTHESIS OF 5-(2-TRIMETHYLSILYLETHOXYCARBONYL)NORBONYLTRICHLOROSILANE:**

[0084] 2-Trimethylsilylethyl 5-norbornene-2-carboxylate (synthesized using known procedures described in U.S. Patent No, 5,985,524 to Allen et al., 23.8 grams, 0.1 mole) and trichlorosilane (10.8 grams, 0.08 mole) were placed in a round bottom flask equipped with a water condenser and nitrogen inlet. The contents were cooled in ice/water bath and platinum(O)-1,3-divinyl-1,1,3,3- tetramethyl disiloxane complex in xylene (100 ml) was added and stirred. After two hours, the bath was removed and the contents stirred at room temperature for 18 hours. ~~Proton-~~ The proton NMR spectrum of the mixture indicated only 50% conversion. The contents were again cooled in the water ice bath and trichlorosilane (6.8 grams, 0.05 mole) and platinum(O)-1,3- divinyl-1,1,3,3- tetramethydisiloxane complex in xylene (100 ml) were added and stirred. After two hours, the bath was removed and the contents stirred at room temperature for 18 hours. Afterwards, the volatiles were removed under vacuum. The colorless liquid thus obtained contained 92% of the desired product 5-(2- trimethylsilylethoxycarbonyl) ~~norbonyltrichlorosilane~~ norbonyltrichlorosilane (2.A) and 8% of the starting material, 2-trimethylsilylethyl 5- norbornene-2-carboxylate. As the starting material would not react in the next step of the reaction, further purification was not necessary.

### **B. HYDROLYSIS OF THE MONOMER MIXTURES :**

[0085] 2-Acetoxy-3,3,3-trifluoropropyltrichlorosilane (1.A above) and 5- (2-trimethylsilylethoxycarbonyl) ~~norbonyltrichlorosilane~~ norbonyltrichlorosilane were mixed together in a molar ratio of 90:10 and hydrolyzed as described in 1.B above.



**EXAMPLE 4**

**POLY[2-HYDROXY-3,3,3-TRIFLUOROPROPYLSILSESQUIOXANE-CO-5-(2-T-BUTOXYCARBONYL)-NORBORNYSILSESQUIOXANE](80:20):-**

**A. SYNTHESIS OF 5-(2-T-BUTOXYCARBONYL)NORBONYLTRICHLOROSILANE:**

**POLY[2-HYDROXY-3,3,3-TRIFLUOROPROPYLSILSESQUIOXANE-CO-5-(2-T-BUTOXYCARBONYL) NORBORNYSILSESQUIOXANE](80:20)**

**A. SYNTHESIS OF 5-(2-T-BUTOXYCARBONYL)NORBONYLTRICHLOROSILANE:**

[0092] Anhydrous hexane (50 ml), t-butyl-5-norbornene-2-carboxylate (9.7 grams, 0.05 mole), and platinum on alumina (5 wt%, 300 mg) were placed in a round bottom flask equipped with a water condenser and nitrogen inlet. Trichlorosilane (13.54 grams, 0.10 mole) was added to this mixture and heated to reflux for 40 hours. Afterwards, the solution was filtered under nitrogen into a flask containing 100 mg of calcium hydride. Solvent and excess trichlorosilane were removed under vacuum. The percentage conversion was estimated by proton NMR and the product was used without further purification.

**APPENDIX B -- REPLACEMENT PARAGRAPHS FOR THE SPECIFICATION**


The following paragraphs incorporate all revisions made in Appendix A, and, as such, are replacement paragraphs for those in the originally filed specification:

A1 [0004] In order to overcome these problems, bilayer resists have been developed. Such bilayer resists are generally comprised of a top thin film imaging layer coated on a thick organic underlayer and are patterned by i) imagewise exposure and development of the top layer, and then (ii) anisotropically transferring the developed pattern in the top layer to the thick underlayer and subsequently to the substrate. The top imaging layer contains a suitable refractory oxide precursor such as silicon, boron or germanium that enables the use of oxygen-reactive ion etching (RIE) in the image transfer step.

A2 [0008] Fluorocarbon polymers, such as polymers prepared from trifluoromethyl-substituted acrylates have been described previously. See, for example, Ito et al. (1981), "Methyl Alpha-Trifluoromethylacrylate, an E- Beam and UV Resist," *IBM Technical Disclosure Bulletin* 24(4):991, Ito et al. (1982) *Macromolecules* 15:915-920, which describes preparation of poly(methyl  $\alpha$ -trifluoromethylacrylate) and poly( $\alpha$ -trifluoromethylacrylonitrile) from their respective monomers, and Ito et al. (1987), "Anionic Polymerization of  $\alpha$ -(Trifluoromethyl)Acrylate," in *Recent Advances in Anionic Polymerization*, T. E. Hogen-Esch and J. Smid, Eds. (Elsevier Science Publishing Co., Inc.), which describes an anionic polymerization method for preparing polymers of trifluoromethylacrylate. Willson et al., *Polymer Engineering and Science* 23(18):1000-1003, also discuss poly(methyl  $\alpha$ -trifluoromethylacrylate) and the use thereof in a positive electron beam resist.


A3 [0019] In one aspect, then, the present invention relates to a fluorocarbonol and/or fluoroacid functionalized silsesquioxane polymer comprised of monomer units having structure (I)

(I)




Within structure (II),  $\text{R}^1$ ,  $\text{R}^2$ ,  $\text{R}^3$  and  $\text{R}^4$  are independently selected from the group consisting of substituents having structure (II)

(II)



wherein  $p$  is 0, 1, or 2,  $s$  is 0, 1, or 2,  $\text{R}^7$  is hydrogen, alkyl or fluoroalkyl,  $\text{R}^8$  is fluoroalkyl,  $\text{R}^9$  is OH, COOH or an acid-cleavable moiety, and  $\text{Q}$  is selected from the group consisting of substituted (e.g., fluorinated) and unsubstituted arylene, substituted (e.g., fluorinated) and unsubstituted cycloalkylene, substituted and unsubstituted alkarylene, and moieties having the structure (III)


(III)



wherein  $\text{R}^5$  and  $\text{R}^6$  are independently hydrogen, alkyl (e.g., linear, branched, or cycloalkyl) or fluoroalkyl and  $n$  is an integer from zero to 4. The polymer may serve as either the base-soluble component of an unexposed resist in a negative resist or as an acid-labile material that releases acid following irradiation in a positive resist.

[0020] In another aspect, the present invention relates to a fluorocarinol and/or fluoroacid functionalized silsesquioxane copolymer comprising monomer units having structure (I), as described above, and monomer units having structure (IV)

(IV)



wherein  $R^{10}$ ,  $R^{11}$ ,  $R^{12}$  and  $R^{13}$  are independently hydrogen, alkyl (e.g., linear, or branched, or cycloalkyl), fluoroalkyl, fluorocarinol, fluoroacid or an acid-cleavable moiety, with the proviso that at least one of  $R^{10}$ ,  $R^{11}$ ,  $R^{12}$  and  $R^{13}$  is an acid-cleavable moiety. The copolymer may serve as an acid-labile material that releases acid following irradiation.

[0023] The present invention also relates to the use of the resist composition in a lithography method. The process involves the steps of (a) optionally coating a substrate with an organic underlayer; (b) coating the organic underlayer with a top layer comprising: i) a radiation sensitive acid generator and ii) a fluorocarinol functionalized silsesquioxane polymer containing polar groups and acid-labile groups; (b) exposing the top layer selectively to a predetermined pattern of radiation to form a latent image therein; (c) developing the image in the top layer using a suitable developer composition; and (e) transferring the image to the substrate. The resist composition may be used to form a single layer photoresist or a bilayer photoresist. The radiation may be ultraviolet, electron beam or x-ray. Ultraviolet radiation is preferred, particularly deep ultraviolet radiation having a wavelength of less than about 250 nm, e.g., 157 nm, 193 nm, or 248 nm. The pattern from the resist structure may then be transferred to the underlying substrate.

Al  
[0024] Typically, the transfer is achieved by reactive ion etching or some other etching technique. Thus, the compositions of the invention and resulting resist structures can be used to create patterned material layer structures such as metal wiring lines, holes for contacts or vias, insulation sections (e.g., damascene trenches or shallow trench isolation), trenches for capacitor structures, etc., as might be used in the design of integrated circuit devices.

A1  
[0025] Fig. 1 is a graph illustrating the optical density of a polymer of the invention at a range of UV wavelengths.

AO  
[0026] Fig. 2 illustrates a polymer of the invention substituted with fluorocarbonol pendent groups.

A9  
[0033] The term "fluorinated" refers to replacement of a hydrogen atom in a molecule or molecular segment with a fluorine atom. The term "fluoroalkyl" refers to an alkyl group wherein at least one hydrogen atom has been replaced with a fluorine atom and includes, for example, trifluoromethyl, difluoromethyl, 2,2,2-trifluoroethyl, pentafluoromethyl, 3,3,3-trifluoromethyl, etc. Similarly, the term "fluorocarbonol" refers to an alcohol moiety in which at least one of the hydrogens bonded to a carbon atom has been replaced with a fluorine atom and includes, for example,  $-\text{CF}_2\text{OH}$ ,  $-\text{CH}(\text{CF}_3)\text{-OH}$ ,  $-\text{C}(\text{CF}_3)_2\text{-OH}$ ,  $-\text{CH}_2\text{CF}_2\text{OH}$ , etc. The term "fluoroacid" refers to a carboxylic acid substituent in which at least one of the hydrogens bonded to a carbon atom has been replaced with a fluorine atom and includes, for example,  $-\text{CF}_2\text{COOH}$ ,  $-\text{CH}(\text{CF}_3)\text{-COOH}$ ,  $-\text{C}(\text{CF}_3)_2\text{-COOH}$ ,  $-\text{CH}_2\text{CF}_2\text{COOH}$ , etc. The term "perfluorinated" is also used in its conventional sense to refer to a molecule or molecular segment wherein all hydrogen atoms are replaced with fluorine atoms. Unless otherwise indicated, "fluorinated" substituents (such as fluoroalkyl and the like) include perfluorinated substituents.

A10  
[0035] The terms "aralkyl" and "alkaryl" refer to moieties containing both alkyl and aryl species, typically containing less than about 24 carbon atoms, and more typically less than about 12 carbon atoms in the alkyl segment of the moiety, and typically containing 1 to 5 aromatic

A10  
2A  
CM


rings. The rings may be either unsubstituted or substituted with 1 or more substituents typically selected from the group consisting of halogen, haloalkyl, alkyl, alkenyl, alkynyl, alkoxy, alkenyloxy, alkynyloxy, alkylthio, aryl, aralkyl, and the like. The term "aralkyl" refers to aryl-substituted alkyl groups, while the term "alkaryl" refers to alkyl-substituted aryl groups. The terms "aralkylene" and "alkarylene" are used in a similar manner to refer to aryl-substituted alkylene and alkyl-substituted arylene moieties.

### THE FLUOROCARBINOL- AND/OR FLUOROACID-FUNCTIONALIZED SILSESQUIOXANE


#### POLYMERS:

A1

[0041] The fluorocarinol- and/or fluoroacid-functionalized silsesquioxane polymer comprised of a monomer unit having structure (I)




Within structure (I), R<sup>1</sup>, R<sup>2</sup>, R<sup>3</sup> and R<sup>4</sup> are independently selected from the group consisting of substituents having structure (II)



wherein p is 0, 1, or 2, s is 0, 1, or 2, R<sup>7</sup> is hydrogen, linear or branched alkyl, or fluoroalkyl, R<sup>8</sup> is fluoroalkyl, R<sup>9</sup> is OH, COOH or an acid-cleavable moiety, and Q is selected from the group consisting of substituted and unsubstituted arylene, substituted and unsubstituted cycloalkylene, substituted and unsubstituted alkarylene, and moieties having the structure (III)

(III)



wherein  $R^5$  and  $R^6$  are independently hydrogen, alkyl (e.g., linear, branched, or cycloalkyl) or fluoroalkyl and  $n$  is an integer from zero to 4.




**[0042]** Preferred  $R^5$  and  $R^6$  substituents are hydrogen,  $C_1$ - $C_6$  alkyl and  $C_1$ - $C_6$  fluoroalkyl. Most preferred  $R^5$  and  $R^6$  substituents are hydrogen, methyl, ethyl and trifluoromethyl-substituted  $C_1$ - $C_6$  alkyl, such as trifluoromethyl, 2,2,2-trifluoroethyl, and 3,3,3-trifluoropropyl.

**[0043]** Preferred  $R^7$  substituents are hydrogen,  $C_1$ - $C_6$  alkyl and  $C_1$ - $C_6$  fluoroalkyl. Most preferred  $R^7$  substituents are hydrogen, methyl, ethyl and trifluoromethyl-substituted  $C_1$ - $C_6$  alkyl, such as trifluoromethyl, 2,2,2-trifluoroethyl, and 3,3,3-trifluoropropyl.

**[0044]** Preferred  $R^8$  substituents are  $C_1$ - $C_6$  fluoroalkyl. Most preferred  $R^8$  substituents are trifluoromethyl-substituted  $C_1$ - $C_6$  alkyl, such as trifluoromethyl, 2,2,2-trifluoroethyl, and 3,3,3-trifluoropropyl.

**[0045]** In the structure (II) substituent,  $R^9$  is -OH, -COOH, or an acid-cleavable moiety, i.e., a molecular moiety that is cleavable with acid, particularly photogenerated acid. Suitable acid-cleavable functionalities include, but are not limited to, esters of the formula  $-(L)_v-(CO)-OR^{14}$ , carbonates of the formula  $-(L)_v-O-(CO)-O-R^{15}$ , and ethers of the formula  $-OR^{16}$ , wherein  $R^{14}$ ,  $R^{15}$  and  $R^{16}$  are selected so as to render the functionality acid-cleavable,  $v$  is zero or 1, and  $L$  is a linking group such as an alkylene group (e.g., linear, branched or cycloalkylene group such as norbornyl or cyclohexylene) a fluoroalkylene group, or an aryl group. In acid-cleavable ester groups, i.e., substituents having the formula  $-(L)_v-(CO)-OR^{14}$ ,  $R^{14}$  is preferably either a tertiary alkyl, e.g., *t*-butyl, a cyclic or alicyclic substituent (generally  $C_7$ - $C_{12}$ ) with a tertiary attachment point such as adamantyl, norbornyl, isobornyl, 2-methyl-2-adamantyl, 2-methyl-2-isobornyl, 2-butyl-2-adamantyl, 2-propyl-2-isobornyl, 2-methyl-2-tetracyclododecenyl, 2-methyl-2-

**[0048]** Examples of substituents having structure (II) include, but are not limited to,







AM [0050] The polymer and copolymer may comprise different monomer units each having structure (I), and, in the case of the copolymer, different monomer units each having structure (IV). The polymer and copolymer may also comprise one or more other monomer units, typically formed from addition polymerizable monomers, preferably vinyl monomers, for example, to enhance the performance of the photoresist. Thus, the polymer and copolymer may comprise minor amounts of acrylic acid or methacrylic acid monomer (e.g., 5-30%) to enhance development.





A18 [0055] Other useful acid generators include the family of nitrobenzyl esters and the s-triazine derivatives. Suitable s-triazine acid generators are disclosed, for example, in U.S. Patent No. 4,189,323. Still other suitable acid generators include N-camphorsulfonyloxynaphthalimide, N-pentafluorophenylsulfonyloxynaphthalimide, ionic iodonium sulfonates, e.g., diaryl iodonium (alkyl or aryl) sulfonate and bis-(di-*t*-butylphenyl)iodonium camphanysulfonate, perfluoroalkanesulfonates, such as perfluoropentanesulfonate, perfluorooctanesulfonate, perfluoromethanesulfonate; aryl (e.g., phenyl or benzyl) triflates and derivatives and analogs thereof, e.g., triphenylsulfonium triflate or bis-(*t*-butylphenyl)iodonium triflate; pyrogallol derivatives (e.g., trimesylate of pyrogallol); trifluoromethanesulfonate esters of hydroxyimides,  $\alpha$ ,  $\alpha'$ -bis-sulfonyl-diazomethanes; sulfonate esters of nitro-substituted benzyl alcohols; naphthoquinone-4-diazides; and alkyl disulfones. Other suitable photoacid generators are disclosed in Reichmanis et al. (1991), *Chemistry of Materials* 3:395, and in U.S. Patent No. 5,679,495 to Yamachika et al. Additional suitable acid generators useful in conjunction with the compositions and methods of the invention will be known to those skilled in the art and/or are described in the pertinent literature.

A19 [0056] The photoresist composition herein comprises both a fluorocarbonol- and/or fluoroacid-functionalized silsesquioxane polymer or copolymer as described in detail above, and an acid generator, with the polymer or copolymer representing up to about 99.5 wt.% of the solids included in the composition, and the photoacid generator representing approximately 0.5-10 wt.% of the solids contained in the composition. The photoresist may take the form of a negative or a positive photoresist and other components and additives may also be present.

A20 [0057] If the photoresist is a positive photoresist, the composition may include a monomeric or polymeric acid-cleavable dissolution inhibitor. When the resist-coated substrate is patternwise exposed to a radiation source, the acid generated by the radiation-sensitive acid generator will cleave the acid-cleavable moieties in the polymer or copolymer and/or in the dissolution inhibitor, thus making the exposed areas of the photoresist composition soluble in conventional developer solutions. If included, the dissolution inhibitor, may be present either as a pendent moiety on the polymer or copolymer chain, as an additional element in the photoresist composition, or as a combination of the two. If a dissolution inhibitor is present, it will typically represent in the range of about 1 wt.% to 40 wt.%, preferably about 5 wt.% to 30 wt.%, of the total solids. Positive photoresist compositions that comprise a dissolution inhibitor need not have acid-cleavable moieties on the silsesquioxane polymer, i.e. R<sup>9</sup> need not be an acid-labile group, as the dissolution inhibitor will independently be sufficient to result in the dissolution of the exposed areas of resist.

A21 [0061] The crosslinking agent may be any suitable crosslinking agent known in the negative photoresist art that is otherwise compatible with the other components of the photoresist composition. The crosslinking agent preferably acts to crosslink the polymer component in the presence of a generated acid. Preferred crosslinking agents are glycoluril compounds such as tetramethoxymethyl glycoluril, methylpropyltetramethoxymethyl glycoluril, and methylphenyltetramethoxymethyl glycoluril, available under the POWDERLINK<sup>(R)</sup> trademark from American Cyanamid Company. Other possible crosslinking agents include, but are not limited to: 2,6-bis(hydroxymethyl)-p-cresol and compounds having the following structures:





A 21  
Cont

including their analogs and derivatives, such as those found in Japanese Laid-Open Patent Application (Kokai) No. 1-293339, as well as etherified amino resins, for example, methylated or butylated melamine resins (N-methoxymethyl- or N-butoxymethyl-melamine respectively) or methylated/butylated glycolurils, for example as can be found in Canadian Patent No.

1 204 547. Combinations of crosslinking agents may be used. The remainder of the composition is composed of a solvent and may additionally, if necessary or desirable, include customary additives such as dyes, sensitizers, additives used as stabilizers and acid-diffusion controlling agents, coating aids such as surfactants or anti-foaming agents, adhesion promoters and plasticizers.

[0061] [separate paragraph deleted and incorporated at the end of paragraph 60]

[0066] Surfactants may be used to improve coating uniformity, and include a wide variety of ionic and non-ionic, monomeric, oligomeric, and polymeric species. Likewise, a wide variety of anti-foaming agents may be employed to suppress coating defects. Adhesion promoters may be used as well; again, a wide variety of compounds may be employed to serve this function. A wide variety of monomeric, oligomeric, and polymeric plasticizers such as oligo- and polyethylene glycol ethers, cycloaliphatic esters, and non-acid reactive steroidally derived materials may be used as plasticizers, if desired.

A23 [0069] The present invention also relates to a process for generating a resist image on a substrate comprising the steps of: (a) coating a substrate with a film comprising the resist composition of the present invention; (b) imagewise exposing the film to radiation; and (c) developing the image. The first step involves coating the substrate with a film comprising the resist composition dissolved in a suitable solvent. Suitable substrates are ceramic, metallic or semiconductive, and preferred substrates are silicon-containing, including, for example, silicon dioxide, silicon nitride, and silicon oxynitride. The substrate may or may not be coated with an organic anti-reflective layer prior to deposition of the resist composition. Alternatively, a bilayer substrate may be employed wherein a resist composition of the invention forms an upper resist layer (i.e., the imaging layer) on top of a bilayer substrate comprised of a base layer and underlayer that lies between the upper resist layer and the base layer. The base layer of the bilayer substrate is comprised of a suitable substrate material, and the underlayer of the bilayer substrate is comprised of a material that is highly absorbing at the imaging wavelength and compatible with the imaging layer. Conventional underlayers include cross-linked poly(hydroxystyrene), polyesters, polyacrylates, fluorinated polymers, cyclic olefin polymers and the like, including diazonaphthoquinone (DNQ)/novolak resist material.

A24 [0073] The third step involves development of the image with a suitable solvent. Suitable solvents include an aqueous base, preferably an aqueous base without metal ions such as the industry standard developer tetramethylammonium hydroxide or choline. In positive photoresist applications, the exposed areas of the photoresist will be soluble, leaving behind the unexposed areas. In negative photoresist applications, the converse is true, i.e., the unexposed regions will be soluble to the developer while the exposed regions will remain. Because the fluorocarbonol- and/or fluoroacid-functionalized silsesquioxane monomer of the photoresist composition is substantially transparent at 157 nm, the resist composition is uniquely suitable for use at that wavelength. However, as stated before, the resist may also be used with wavelengths of 193 nm, 248 nm, 254 nm and 365 nm, or with electro beam or x-ray radiation.

**C. SYNTHESIS OF POLY(2-ACETOXY-3,3,3-TRIFLUOROPROPYLSILSESQUIOXANE):**

A25  
[0082] The product from step 1.B was dissolved in toluene (19 grams) and placed in a round bottom flask equipped with a Dean-Stark water separator (to remove the water produced during condensation-reaction) and a water condenser. To this solution, potassium hydroxide (38 mg) was added and the mixture was heated for 18 hours. Afterwards, the solution was filtered through a frit funnel and the solvent was removed in a rotary evaporator. The polymer was then dried under vacuum (16.5 grams).

**D. SYNTHESIS OF POLY(2-HYDROXY-3,3,3-TRIFLUOROPROPYLSILSESQUIOXANE):**

A26  
[0083] Methanol (50 ml) and ammonium hydroxide (30% solution in water, 11 ml) were added to the polymer product of step 1.C and the resultant solution heated to mild reflux for 1 hour. The solution was then cooled to room temperature and added dropwise into a mixture of water (735 ml) and concentrated hydrochloric acid (15 ml). The resultant precipitated polymer (coagulated) was separated by decantation, rinsed with water (2X100 ml) and dried in a vacuum oven at 80 °C for two hours. This polymer was then powdered, transferred into a frit funnel and washed with water (3X100 ml). Then it was dried in a vacuum oven at 80 °C for 24 hours. Yield: 8.5 grams, Mw 3,500. Optical Density (OD) of this polymer as thin film is 0.6/micrometer.

**EXAMPLE 2**

A27  
**POLY(2-HYDROXY-3,3,3-TRIFLUOROPROPYLSILSESQUIOXANE-CO- 5-(2-TRIMETHYLSILYLETHOXYCARBONYL)NORBORNYSILSESQUIOXANE)(90:10):**

**A. SYNTHESIS OF 5-(2- TRIMETHYLSILYLETHOXYCARBONYL)NORBORNYLTRICHLOROSILANE:**

[0084] 2-Trimethylsilylethyl 5-norbornene-2-carboxylate (synthesized using known procedures described in U.S. Patent No, 5,985,524 to Allen et al., 23.8 grams, 0.1 mole) and trichlorosilane (10.8 grams, 0.08 mole) were placed in a round bottom flask equipped with a water condenser and nitrogen inlet. The contents were cooled in ice/water bath and platinum(O)-1,3-divinyl-1,1,3,3- tetramethyl disiloxane complex in xylene (100 ml) was added and stirred. After two hours, the bath was removed and the contents stirred at room temperature for 18 hours. The proton NMR spectrum of the mixture indicated only 50% conversion. The contents were again

A27  
cont

cooled in the water ice bath and trichlorosilane (6.8 grams, 0.05 mole) and platinum(O)-1,3-divinyl-1,1,3,3- tetramethydisiloxane complex in xylene (100 ml) were added and stirred. After two hours, the bath was removed and the contents stirred at room temperature for 18 hours. Afterwards, the volatiles were removed under vacuum. The colorless liquid thus obtained contained 92% of the desired product 5-(2- trimethylsilylethoxycarbonyl) norbornyltrichlorosilane (2.A) and 8% of the starting material, 2-trimethylsilylethyl 5-norbornene-2-carboxylate. As the starting material would not react in the next step of the reaction, further purification was not necessary.

---

A28

**B. HYDROLYSIS OF THE MONOMER MIXTURES :**

[0085] 2-Acetoxy-3,3,3-trifluoropropyltrichlorosilane (1.A above) and 5- (2-trimethylsilylethoxycarbonyl) norbornyltrichlorosilane were mixed together in a molar ratio of 90:10 and hydrolyzed as described in 1.B above.

---

**EXAMPLE 4**

**POLY[2-HYDROXY-3,3,3-TRIFLUOROPROPYLSILSESQUIOXANE-CO-5-(2-T-BUTOXYCARBONY) NORBORNYSILSESQUIOXANE](80:20)**

A29

**A. SYNTHESIS OF 5-(2-T-BUTOXYCARBONYL)NORBORNYLTRICHLOROSILANE:**


[0092] Anhydrous hexane (50 ml), t-butyl-5-norbornene-2-carboxylate (9.7 grams, 0.05 mole), and platinum on alumina (5 wt%, 300 mg) were placed in a round bottom flask equipped with a water condenser and nitrogen inlet. Trichlorosilane (13.54 grams, 0.10 mole) was added to this mixture and heated to reflux for 40 hours. Afterwards, the solution was filtered under nitrogen into a flask containing 100 mg of calcium hydride. Solvent and excess trichlorosilane were removed under vacuum. The percentage conversion was estimated by proton NMR and the product was used without further purification.

---

APPENDIX C - AMENDMENTS TO THE CLAIMS

Cancel claims 1-66 without prejudice and replace them with the following new claims:

--67. A fluorinated silsesquioxane polymer comprised of monomer units having the structure (I)



wherein:

$R^1$ ,  $R^2$ ,  $R^3$  and  $R^4$  are independently selected from the group consisting of substituents having a terminal  $-CR^7R^8R^9$  group;

$R^7$  is hydrogen, alkyl, or fluoroalkyl;

$R^8$  is fluoroalkyl; and

$R^9$  is OH, COOH or an acid-cleavable moiety.

68. The polymer of claim 67, wherein  $R^1$ ,  $R^2$ ,  $R^3$  and  $R^4$  are independently selected from the group consisting of substituents having the structure of formula (II)



wherein n is zero or 1.

69. The polymer of claim 68, wherein Q is selected from the group consisting of substituted and unsubstituted arylene, substituted and unsubstituted cycloalkylene, and  $C_1-C_4$

alkylene optionally substituted with at least one nonhydrogen substituent selected from alkyl and fluoroalkyl.

70. The polymer of claim 69, wherein Q is fluorinated.

71. The polymer of claim 69, wherein Q is selected from the group consisting of arylene, fluorinated arylene, cycloalkylene, fluorinated cycloalkylene, and C<sub>1</sub>-C<sub>4</sub> alkylene optionally substituted with 1-8 nonhydrogen substituents selected from alkyl and fluoroalkyl.

72. The polymer of claim 71, wherein Q is selected from the group consisting of arylene, fluorinated arylene, cycloalkylene, and fluorinated cycloalkylene.

73. The polymer of claim 72, wherein Q is arylene or fluorinated arylene.

74. The polymer of claim 73, wherein Q is bicyclic.

75. The polymer of claim 73, wherein Q is arylene.

76. The polymer of claim 73, wherein Q is fluorinated arylene.

77. The polymer of claim 72, wherein Q is cycloalkylene.

78. The polymer of claim 72, wherein Q is fluorinated cycloalkylene.

79. The polymer of claim 71, wherein Q is C<sub>1</sub>-C<sub>4</sub> alkylene optionally substituted with 1-8 nonhydrogen substituents selected from alkyl and fluoroalkyl.

80. The polymer of claim 79, wherein Q is C<sub>1</sub>-C<sub>4</sub> alkylene optionally substituted with 1-8 nonhydrogen substituents selected from C<sub>1</sub>-C<sub>6</sub> alkyl and C<sub>1</sub>-C<sub>6</sub> fluoroalkyl.



81. The polymer of claim 79, wherein Q is C<sub>1</sub>-C<sub>4</sub> alkylene optionally substituted with 1-8 nonhydrogen substituents selected from C<sub>1</sub>-C<sub>6</sub> alkyl, trifluoromethyl, and trifluoromethyl-substituted C<sub>1</sub>-C<sub>6</sub> alkyl.

82. The polymer of claim 67, wherein R<sup>7</sup> is hydrogen, C<sub>1</sub>-C<sub>6</sub> alkyl, or C<sub>1</sub>-C<sub>6</sub> fluoroalkyl.

83. The polymer of claim 67, wherein R<sup>7</sup> is hydrogen, C<sub>1</sub>-C<sub>6</sub> alkyl, trifluoromethyl, or trifluoromethyl-substituted C<sub>1</sub>-C<sub>6</sub> alkyl.

84. The polymer of claim 67, wherein R<sup>8</sup> is C<sub>1</sub>-C<sub>6</sub> fluoroalkyl.

85. The polymer of claim 83, wherein R<sup>8</sup> is trifluoromethyl-substituted C<sub>1</sub>-C<sub>6</sub> alkyl.

86. The polymer of claim 67, wherein R<sup>9</sup> is OH.

87. The polymer of claim 67, wherein R<sup>9</sup> is COOH.

88. The polymer of claim 67, wherein R<sup>9</sup> is an acid-cleavable moiety.

89. The polymer of claim 88, wherein the acid-cleavable moiety is an acid-cleavable ester, ether or carbonate.


90. The polymer of claim 89, wherein R<sup>9</sup> is an acid-cleavable ester.

91. The polymer of claim 90, wherein R<sup>9</sup> has the formula -(L)<sub>v</sub>-(CO)-OR<sup>14</sup> wherein v is zero or 1, L is a linking group, and R<sup>14</sup> is selected from the group consisting of tertiary alkyl moieties, cyclic or alicyclic substituents with a tertiary attachment point, and 2-trialkylsilylethyl moieties.

92. The polymer of claim 91, wherein v is zero and R<sup>14</sup> is tertiary alkyl.

93. The polymer of claim 92, wherein  $R^{14}$  is *t*-butyl.
94. The polymer of claim 91, wherein  $v$  is zero and  $R^{14}$  is a cyclic or alicyclic substituent with a tertiary attachment point.
95. The polymer of claim 94, wherein  $R^{14}$  is selected from the group consisting of adamantyl, norbornyl, isobornyl, 2-methyl-2-adamantyl, 2-methyl-2-isobornyl, 2-butyl-2-adamantyl, 2-propyl-2-isobornyl, 2-methyl-2-tetracyclododecenyl, 2-methyl-2-dihydrodicyclopentadienyl-cyclohexyl, 1-methylcyclopentyl, 1-methylcyclohexyl, 2-trimethylsilylethyl, and 2-triethylsilylethyl.
96. The polymer of claim 91, wherein  $v$  is zero and  $R^{14}$  is 2-trialkylsilylethyl.
97. The polymer of claim 96, wherein  $R^{14}$  is 2-trimethylsilylethyl.
98. The polymer of claim 96, further comprising additional monomer units having the structure of formula (IV)

(IV)



wherein  $R^{10}$ ,  $R^{11}$ ,  $R^{12}$  and  $R^{13}$  are independently hydrogen, alkyl, fluoroalkyl, fluorocarbonol or an acid-cleavable moiety, with the proviso that at least one of  $R^{10}$ ,  $R^{11}$ ,  $R^{12}$  and  $R^{13}$  is an acid-cleavable moiety.

99. The polymer of claim 98, wherein at least one of  $R^{10}$ ,  $R^{11}$ ,  $R^{12}$  and  $R^{13}$  is selected from the group consisting of acid-cleavable esters, ethers, and carbonates.

100. The polymer of claim 99, wherein at least one of  $R^{10}$ ,  $R^{11}$ ,  $R^{12}$  and  $R^{13}$  is an acid-cleavable ester.

101. A lithographic photoresist composition comprising the fluorinated silsesquioxane polymer of claim 67 and a radiation-sensitive acid generator.

102. A lithographic photoresist composition comprising the fluorinated silsesquioxane polymer of claim 98 and a radiation-sensitive acid generator.

103. The lithographic photoresist composition of claim 101, wherein the photoresist composition is a positive resist and further comprises a photoacid-cleavable dissolution inhibitor.

104. The lithographic photoresist composition of claim 102, wherein the photoresist composition is a positive resist and further comprises a photoacid-cleavable dissolution inhibitor.

105. The lithographic photoresist composition of claim 101, wherein the photoresist composition is a negative resist and further comprises a crosslinking agent.

106. The lithographic photoresist composition of claim 102, wherein the photoresist composition is a negative resist and further comprises a crosslinking agent.

107. The lithographic photoresist composition of claim 105, wherein the crosslinking agent is a glycoluril compound.

108. The lithographic photoresist composition of claim 107, wherein the glycoluril compound is selected from the group consisting of tetramethoxymethyl glycoluril, methylpropyltetramethoxymethyl glycoluril, methylphenyltetramethoxymethyl glycoluril, and mixtures thereof.

109. The lithographic photoresist composition of claim 106, wherein the crosslinking agent is a glycoluril compound.

110. The lithographic photoresist composition of claim 109, wherein the glycoluril compound is selected from the group consisting of tetramethoxymethyl glycoluril, methylpropyltetramethoxymethyl glycoluril, methylphenyltetramethoxymethyl glycoluril, and mixtures thereof.

111. A process for generating a resist image on a substrate, comprising the steps of:

- (a) coating a substrate with a film of the photoresist composition of claim 101;
- (b) exposing the film selectively to a predetermined pattern of deep ultraviolet radiation so as to form a latent, patterned image in the film; and
- (c) developing the latent image with a developer.

112. The process of claim 111, wherein the deep ultraviolet radiation has a wavelength of less than 250 nm.

113. The process of claim 112, wherein the deep ultraviolet radiation has a wavelength of 157 nm.

114. The process of claim 111, wherein the substrate is a bilayer substrate comprising a base layer covered by an underlayer and the photoresist composition covers the underlayer.

115. A process for generating a resist image on a substrate, comprising the steps of:

- (a) coating a substrate with a film of the photoresist composition of claim 102;

- (b) exposing the film selectively to a predetermined pattern of deep ultraviolet radiation so as to form a latent, patterned image in the film; and
- (c) developing the latent image with a developer.

116. The process of claim 115, wherein the deep ultraviolet radiation has a wavelength of less than 250 nm.

117. The process of claim 116, wherein the deep ultraviolet radiation has a wavelength of 157 nm.

118. The process of claim 115, wherein the substrate is a bilayer substrate comprising a base layer covered by an underlayer and the photoresist composition covers the underlayer.

119. A method of forming a patterned material structure on a substrate, comprising:
- (a) providing a substrate comprised of a material selected from the group consisting of semiconductors, ceramics and metals;
  - (b) applying a layer of the photoresist composition of claim 103 to the substrate;
  - (c) patternwise exposing the substrate to radiation whereby acid is generated by the radiation-sensitive acid generator in exposed regions of the photoresist layer;
  - (d) contacting the substrate with an aqueous alkaline developer solution, whereby the exposed regions of the photoresist layer are selectively dissolved by the developer solution to reveal a resist structure pattern; and
  - (e) transferring the resist structure pattern to the substrate by etching into the substrate through spaces in the resist structure pattern.

120. The process of claim 119, wherein the radiation is deep ultraviolet radiation.

121. A method of forming a patterned material structure on a substrate, comprising:
- (a) providing a substrate comprised of a material selected from the group consisting of semiconductors, ceramics and metals;

- (b) applying a layer of the photoresist composition of claim 104 to the substrate;
- (c) patternwise exposing the substrate to radiation whereby acid is generated by the radiation-sensitive acid generator in exposed regions of the photoresist layer;
- (d) contacting the substrate with an aqueous alkaline developer solution, whereby the exposed regions of the photoresist layer are selectively dissolved by the developer solution to reveal a resist structure pattern; and
- (e) transferring the resist structure pattern to the substrate by etching into the substrate through spaces in the resist structure pattern.

122. The process of claim 119, wherein the radiation is deep ultraviolet radiation.

123. A method of forming a patterned material structure on a substrate, comprising:

- (a) providing a substrate comprised of a material selected from the group consisting of semiconductors, ceramics and metals;
- (b) applying a layer of the photoresist composition of claim 105 to the substrate
- (c) patternwise exposing the substrate to radiation whereby acid is generated by the radiation-sensitive acid generator in exposed regions of the photoresist layer thereby inducing crosslinking;
- (d) contacting the substrate with an aqueous alkaline developer solution, whereby the unexposed regions of the photoresist layer are selectively dissolved by the developer solution to reveal a negative resist structure pattern; and
- (e) transferring the negative resist structure pattern to the substrate by etching into the substrate through spaces in the negative resist structure pattern.

124. A method of forming a patterned material structure on a substrate, comprising:

- (a) providing a substrate comprised of a material selected from the group consisting of semiconductors, ceramics and metals;
- (b) applying a layer of the photoresist composition of claim 106 to the substrate

(c) patternwise exposing the substrate to radiation whereby acid is generated by the radiation-sensitive acid generator in exposed regions of the photoresist layer thereby inducing crosslinking;

(d) contacting the substrate with an aqueous alkaline developer solution, whereby the unexposed regions of the photoresist layer are selectively dissolved by the developer solution to reveal a negative resist structure pattern; and

(e) transferring the negative resist structure pattern to the substrate by etching into the substrate through spaces in the negative resist structure pattern.--